

TERAFLEX

INSTALLATION NOTES

Wheel Spacers and Adapters for Jeep Wrangler JK Fits all models 2007

Part #001055000 for wheel spacer

Part #001055010 for wheel spacer and adapter



NOTICE: Wheel spacers must be retorqued after the first 100 miles, and again each time the tires are rotated (5000 miles).

It is the installers responsibility to ensure the correct use and application of wheel spacers and adapters. Use only with DOT approved wheels and hardware. Not recommended for wheels wider than 8 inches.

Tera Manufacturing, Inc.
5251 South Commerce Dr.
Murray, Utah 84107
Phone/801.288.2585
Fax/801.713.2313
www.teraflex.biz

WARNING: Neither the seller nor the manufacturer will be liable for any loss, damage, or injury directly or indirectly arising from the use of or inability to determine the use of these products. Before using, the user shall determine the suitability of the products for its intended use, and the user shall assume all responsibility and risk in connection therewith.

Important Notes!

Some JK factory rear studs are longer than 1.25 inches. Carefully grind down the end of the stud (the dog point where there are no threads) to reduce the overall length to slightly less than 1.25 inches without damaging the threads.

JK Wheel adapter studs must be carefully pressed into either the 4.5 or 5.5 diameter bolt circle depending on your wheels of choice. Use an arbor press or other similar device to install the studs. Wheel spacer studs come pre-installed.

After installing the wheel spacer/adapater, use a straight edge to ensure that the factory studs are below the flat surface where the wheel mounts to the spacer/adapter

Note: You can test fit the spacer/adapter first. If the studs are below the surface then do not grind the end of the factory stud.

