



**INSTALLATION INSTRUCTIONS
07 JEEP WRANGLER 4DOOR
TAILLIGHT GUARDS
PART NUMBER #JK-7133**

PART LIST

1	Right side taillight guard
1	Left side taillight guard
8	5MM washers
8	Rubber Washers
6	M4x45mm Self Tapping Screws
2	M5x50mm Self Tapping Screws

PROCEDURE:

- 1. REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT. READ INSTRUCTIONS CAREFULLY.**
- Using a Phillips screwdriver remove the two short screws facing the inside of the vehicle from one of the taillight lenses. See figure 1. Then remove the lower screw toward the outside of the car. Note that these factory screws will be replaced by #6x45mm Self Tapping Screws and #8x50mm Self Tapping Screws provided in the Hardware Kit. See figure 2.
- Identify the correct guard for the side of the vehicle you are working on. See figures 3 and 4.
- Install the upper screw (one of the shorter ones) into the hole of the upper mounting bracket.
- Position the guard while inserting the screw into its hole in the lens. Install the screw tightly enough to keep the guard in place.
- Install the other two screws. Align the guard with the top of the lens and tighten the screws using a Phillips screwdriver. Avoid over tightening to prevent damage
- Repeat operation with the other side of the vehicle and check that the two guards are parallel to each other.



Figure 1



Figure 3



Figure 2