

# **Hi-Lift® TUBE MOUNT**

## **ADJUSTABLE FOR 1" - 2" DIAMETER TUBING**

- **Mount your Hi-Lift® jack to round or square tube bumpers, bull bars, roll cages, and roof racks.**
- **Manufactured of 6061-T6 structural aluminum with stainless steel hardware. No drilling!**

# Hi-Lift® TUBE MOUNT

**ADJUSTABLE FOR  
1" - 2" DIAMETER TUBING**



#### EACH UNIT INCLUDES:

- 2 ea. Aluminum Brackets
- 2 ea. Aluminum Knobs
- 2 ea. Long "V" Bolts
- 2 ea. Short "V" Bolts
- 4 ea. 5/16" Hex Nuts
- 4 ea. 5/16" Flat Washers
- 4 ea. 5/16" Lock Washers
- 2 ea. 1/2" Lock Washers

(Secure Brackets as shown)

Secure "V" Bolts to Aluminum Brackets with 5/16" Flat Washer, then 5/16" Lock Washer, and 5/16" Hex Nut.

Fully tighten hardware once the Tube Mount locations are adjusted correctly.



#### INSTALLATION INSTRUCTIONS

**Use Short "V" Bolts for 1" - 1-1/2" Tubing Applications**

**Use Long "V" Bolts for 1-1/2" - 2" Tubing Applications**

(Secure Hi-Lift as shown)

Place Hi-Lift jack on Tube Mount Assembly with Tube Mount Bolts through holes on the Steel Jack Bar. Secure tightly with 1/2" Lock Washer and Aluminum Knob.



**Hi-Lift Jack Company**  
P.O. Box 228  
Bloomfield, IN 47424  
Toll Free (800) 233-2051  
Direct (812) 384-4441  
[www.hi-lift.com](http://www.hi-lift.com)

**UPC CODE**

**Part #TM-700**