

2007-14 JEEP JK PEDAL COVERS

FOR PART #'S: JP-180025-BL & JP-180026-BL

INSTALLATION INSTRUCTIONS PAGE 1 OF 1

TOOLS YOU'LL NEED FOR INSTALLATION

- Drill
- 3/16" drill bit
- Hammer,
- Drift
- Center punch
- Safety glasses
- Catch mat
- 2.5mm allen wrench
- 7mm hex wrench

WARNING!

Always wear gloves and protective eye-wear when operating a drill of any kind.

WARNING!

If any part of this installation seems beyond your level of installation experience, please seek the help of a certified professional.



Manual Pedal Covers



INSTALLATION

For Brake & Clutch Pedals

1. Lay down a blanket or "catch mat" underneath your work area to collect metal shavings from drilling.
2. Remove factory rubber pedal covers.
3. Cover top surface of pedals with masking tape to prevent scratching
4. Place appropriate pedal cover centered on top of pedal on vehicle and use a punch to mark center point to drill
5. Remove billet cover and drill 3/16" holes where marked. Make sure to drill perpendicular to surface. Debur back side of pedal when done drilling.
6. Remove masking tape and place billet pedal cover onto pedals.
7. Secure using hardware provided.

Enjoy your new pedals from Drake Off Road!



Automatic Pedal Covers



Manual Pedal covers