

ONE BELT ON AND OFF-ROAD

THE BEAM'S TRI-LOCK SEATBELT SYSTEM IS THE ANSWER FOR JEEP ENTHUSIASTS WHO WANT TO DRIVE TO WORK AND TO THEIR FAVORITE REMOTE GET-A-WAYS.

ON-ROAD THE TRI-LOCK RESPONDS TO QUICK STOPS OR UNEVEN TERRAIN, BUT OFF-ROAD THIS BELT WILL LOCK YOU DOWN FOR EVEN THE ROUGHEST RIDES.

THE BEAM'S TRI-LOCK SEATBELT CONVENIENTLY RETRACTS UNLIKE 4-POINT RESTRAINTS THAT ARE ALWAYS IN THE WAY. JUST LIKE YOU, THE TRI-LOCK IS READY TO GO OFF-ROAD ANYTIME!



TRI-LOCK™ SEATBELT SYSTEM

SWITCHING SEATBELT MODES

THE TRI-LOCK SEATBELT WILL BE IN NORMAL "ON-ROAD" MODE UNTIL YOU MANUALLY MAKE A CHANGE IN THE LOCKING MECHANISM.

- 1. SWITCHING TO OFF-ROAD MODE:** PULL THE SEATBELT ALL THE WAY OUT, THEN GRADUALLY LET THE SEATBELT RECOIL (YOU SHOULD HEAR A CLICKING SOUND) UNTIL YOU ARE LOCKED IN SECURELY.
- 2. TO RETURN TO ON-ROAD OPERATION:** UNLATCH THE SEATBELT BUCKLE AND LET THE SEATBELT FULLY REWIND.

JEEP TRI-LOCK INSTALLATION INSTRUCTIONS

1. UNBOLT AND REMOVE THE O.E. BUCKLE. ON YJ JEEPS, BUCKLES WILL MOUNT TO THE FLOOR; TJ BUCKLES WILL MOUNT TO THE SEAT.
2. ON YJ JEEPS, REMOVE THE O.E. BUCKLE SLEEVE AND FEED THE NEW BUCKLE SIDE INTO THE SLEEVE.
3. MOUNT THE NEW SEATBELT BUCKLE SIDE TO THE VEHICLE USING O.E. MOUNTING HOLES AND HARDWARE.
4. UNBOLT AND REMOVE THE SEATBELT RETRACTOR AND LAP BELT ANCHOR; LOCATED BEHIND THE DOOR OPENING NEAR THE FLOOR. ON MOST VEHICLES, ONE BOLT WILL HOLD BOTH THE RETRACTOR AND THE LAP BELT ANCHOR. ON EARLY YJ'S, THEY ARE SECURED BY SEPARATE MOUNTING BOLTS.
5. UNBOLT AND REMOVE THE SHOULDER LOOP MOUNTED HIGH ON THE ROLL BARS. THE SEATBELT MAY NOW BE COMPLETELY REMOVED FROM THE VEHICLE.
6. MOUNT THE NEW SEATBELT RETRACTOR AND THE LAP BELT ANCHOR USING THE O.E. MOUNTING HOLES AND HARDWARE. ON MOST JEEPS, BOTH OF THESE WILL MOUNT IN THE SAME HOLE.
7. MOUNT THE SHOULDER LOOP USING THE O.E. MOUNTING HOLES AND HARDWARE.
8. INSPECT THE SEATBELT PATH FOR OBSTACLES THAT COULD ABRASE OR DAMAGE THE WEBBING.

NOTE: AS YOU ARE WORKING, INSPECT ALL MOUNTING LOCATIONS FOR RUST AND DAMAGE. WHERE NECESSARY, REINFORCE THE FLOOR OR OTHER MOUNTING LOCATIONS.

BEAM'S

S E A T B E L T S

seatbelts.net

405.793.0505

© Beam's Industries 2011.