



Installation Instructions

PART#:86448and 86648
Rear Bumper Guard for Jeep Wrangler 4Door 2007-10

PARTS LIST

1	Bumper
2	Brackets
2	Bolt plates
10	12MM X 35MM bolts
12	12MM washers
6	12MM lock nuts
4	12MM lock washers

PROCEDURE:

- 1. REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT. READ INSTRUCTIONS CAREFULLY.**
2. Locate, remove and set aside the brackets (Fig 1)
3. Remove factory bumper by removing the side brackets (Fig 2) and the bolts in the removable brackets (Fig 3)
4. Insert the driver side bracket into the frame (Fig 3)
5. Start the two 12MM bolts and thick washers through the bolt plate and into the frame.
6. Repeat the bracket installation on the passenger side of the vehicle.
7. Insert a thin piece of wood between the bumper and the trailer hitch receiver to prevent damage. (Fig 4)
8. Position the bumper in between the two mounts and start the six 12MM bolts, washers and locking nuts. (Fig 5)
9. Level the bumper and tighten all the fasteners. (Fig 6)


Fig 1



Driver side bracket

Passenger side bracket

Fig 2



Factory bumper bracket



Fig 3

Removable
bracket (leave on)

Bumper bracket



Fig 4



Fig 5



Fig 6

Rampage Products, LLC 9225 Stellar Court Unit C, Corona, CA 92883-4919
Phone: (951) 277-4949 Fax: (951) 277-2295
Web: info@rampageproducts.net
Made in China