



Model No.: PKC0RA

# Wireless Back-Up Camera and Monitor

## OWNER'S MANUAL & WARRANTY INFORMATION



**IMPORTANT:**  
READ THESE INSTRUCTIONS BEFORE USE AND RETAIN FOR FUTURE REFERENCE.

Dear Customer,  
CONGRATULATIONS. The PKC0RA Wireless Back-Up Camera and Monitor, when used as described, will improve your ability to see behind your car, truck, RV, or mini-van. We have taken numerous measures in quality control to ensure that your product arrives in top condition, and will perform to your satisfaction.

### Before You Install

Some states or local governments may have regulations or laws that restrict the use of anything that might impair the clear view of a license plate. Please check local laws for compliance.

Automotive video equipment installations can be difficult at times, even to the most experienced of installation technicians. If you are not confident working with 12 volt DC vehicle wiring, removing and reinstalling interior panels, carpeting, dashboards or other components of your vehicle, contact the vehicle's manufacturer, or consider having the Wireless Back-Up Camera and Monitor professionally installed.

**⚠ This device, as well as all other wireless devices, may be subject to interference. Interference may be caused by cell phones, Bluetooth headsets, Wi-Fi routers, power lines and other various electrical equipment, etc.**

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

### Parts

1. Monitor and Mounting Arm



2. Camera



3. Transmitter Box



4. Camera Mounting Accessories



5. Monitor Power Cable



6. Transmitter Box Power Cable



## Installation

These instructions do not apply to all vehicles. They are only meant as a general guide due to the number of different makes & models.

For vehicle specific questions contact your vehicle's manufacturer.

### MONITOR INSTALLATION

When choosing a location to mount the monitor, make sure the monitor is in an area that will not obstruct your vision while driving.

#### Choose a Location and Install Power Cable



1. Temporarily place the monitor in the location that you have chosen.
2. Route the power cable to the vehicle's cigarette lighter socket/12V power outlet. The cable must not interfere with the safe operation of the vehicle.



#### Mounting the Monitor

Before mounting the monitor, clean the mounting surface well.

1. Position the suction mount to the smooth surface which suits your requirement.
2. Press the suction cap against the smooth surface such as windshield or dashboard.
3. Press the lock down to attach and fix the mount to the surface.
4. Snap in the monitor to the suction mount.
5. Adjust the mounting arms to suit your view angle to the monitor and tighten the screws on the mount to fix the position.



To maximize the effectiveness of the suction mount, it is recommended that the application be performed under the following conditions:

Surface temperature should be between 70°F and 100°F (21°C and 38°C).

Application below 50°F (10°C) should be avoided.

Application should not occur in direct sunlight.

Mounting should be protected from exposure to direct sunlight for a period of 24 hours.

NOTE: UNDER EXTREME BRIGHT LIGHT CONDITIONS, THE SCREEN IMAGE MAY TAKE A FEW SECONDS TO STABILIZE. PLEASE WAIT UNTIL THE IMAGE HAS STABILIZED BEFORE BACKING UP.

### MONITOR POWER CONNECTION

Use the 12 Volt cigarette lighter adaptor plugged into the vehicle's cigarette lighter socket.

#### Power Cable with 12 Volt Cigarette Lighter Adaptor


1. Insert the small 12 Volt DC plug of the power cable into the right side of the monitor.
2. Plug the 12 Volt cigarette lighter adaptor into the vehicle's cigarette lighter socket.
3. The monitor's factory default setting is with the power ON or STANDBY mode. You may switch between power ON (STANDBY) or OFF by pressing the power button.

## CAMERA INSTALLATION

You can mount the camera using the top or bottom mounting bolts or screws of license plate. Ensure the camera viewing is not obstructed. The supplied wedge shaped spacers can adjust the camera mounting angle vertically.




1. Loosen the license plate bolts or screws and remove the rear license plate.
2. Insert each license plate bolt into a supplied wedge shaped spacer, through the bolt holes of the camera, and through the remaining wedge shaped spacer and the license plate.



3. Align the holes on vehicle and temporarily tighten the license plate bolts/screws. The wedge shaped spacers will make the camera face downward.
4. Choose a routing path for the camera's power cable through the vehicle's body to the reverse light circuit. If in doubt, seek professional installation assistance.
5. Some vehicles may have a hole to pass the wire through. For example, the location where the license plate light is mounted, or you can drill a hole close to the power cable that will attach to the camera. Once you have determined where the cable will enter the vehicle's trunk, remove the camera. If you are able to use an existing opening or hole, skip the next two steps.
6. If you are going to drill a hole, choose a location as close to the camera where the power cable comes out. Before you drill a hole you MUST CHECK WHAT IS BEHIND THE DRILLING LOCATION. If there are any vehicle components, like electrical parts or fuel system components behind the drilling location, you must take precaution not to damage them. Remove the license plate and camera before drilling.
7. After you have drilled a half inch (1/2") hole, pass the camera wire connector through the hole into the vehicle and place the grommet in the hole around the camera wire. You must use the grommet to prevent the metal edge of the hole from cutting the camera cable.
8. Mount the transmitter box inside the trunk. Connect the camera cable and the power cable to the transmitter box.
9. Find the vehicle's reverse lights. Turn the vehicle's ignition key to the accessory position, engage the parking brake and put the car in reverse. Look at the vehicle's tail lights to see where the reverse white lights are located.  
To locate the reverse light's 12V+ wire, it is necessary to access to the rear part of the vehicle's tail light.

For help locating the vehicle's reverse light circuit, contact your vehicle's manufacturer for vehicle specific wiring diagrams.


10. Once you have located the reverse light circuit, you need to route the power cable supplied to that location. Fasten the power cable securely to prevent it from being caught on any vehicle component like the trunk hinge. **Never** route the cable on the outside of the vehicle.
11. Locate reverse light socket and remove light bulb. There are two wires connected to the reverse light sockets on most vehicles. Usually the negative wire is black and the positive wire is a colored wire. If you are uncertain about the wiring, use a 12 volt multimeter (available at most auto parts stores) to determine which wire is positive. Follow the manufacturer's instructions for the safe use of the multimeter.



12. After determining which wire is the positive and which is the negative, turn off the ignition key, then remove the battery's negative cable.
13. Splice the red wire using the supplied wire clamp to the reverse light's positive (+) wire. Use a set of slip joint pliers to squeeze the METAL BLADE and ensure good connection of both wires.




Insert the existing wire to be tapped to the clamp.



Insert the wire to be attached to the clamp.




Crimp clamp with pliers, then close lock.



Wire clamp after locking

14. You may not need to use the wire clamp. The power cable can be wired directly to the reverse light circuit by stripping the reverse light wires then twisting the camera wires to the exposed reverse light wires. Once connected, wrap with electrical tape. Do not attempt this if you are not knowledgeable with electrical installation practices. If in doubt, seek professional installation assistance.
15. Next splice the black wire of the camera's power cable to the reverse light's negative (-) wire or ground.
16. Replace the reverse light bulb and re-install the light socket. Secure all the wires with cable ties or electrical tape. Reattach the negative battery cable to the battery afterwards.

## MONITOR CONTROLS



Make sure the monitor is powered ON (STANDBY), then the monitor will automatically show the camera's image when the vehicle is in reverse gear. Also, there are 4 control buttons available for user to have their controls.

### BLUE LED Power Indicator

When the monitor is ON the blue LED will be lit. If there is power to the monitor, but the monitor is OFF, the blue LED will be OFF.

### Power Button

Press the Power button to turn the display ON; the blue LED will be lit to indicate the monitor is ON. Press it again to turn the display OFF; the blue LED will turn off.

### Contrast Control

There are 10 levels of contrast. To adjust the contrast, press the Contrast Control button. Pressing the button to increase the contrast at the highest level will return to the lowest level.

### Brightness

There are 10 levels of brightness. To adjust the brightness, press the Brightness Control button. Pressing the button to increase the brightness at the highest level will return to the lowest level.

## TESTING THE SYSTEM

1. Reattach the vehicle's negative battery cable.
2. Turn the ignition key to the accessory position; do not start the vehicle.
3. Engage the parking brake, then put the shifter in the reverse position.
4. Turn the monitor ON by pressing the ON/OFF button on the monitor.
5. Look at the monitor; if the image does not match your rear view mirror press the Image Orientation button on the monitor to correct the image.

After testing the unit and you are satisfied with the route you have chosen for the cabling, you must permanently install it.

Fully tighten the license plate bolts.

Route all wires behind interior panels or under carpeting so they are hidden.

Use supplied cable ties to neatly gather any excess wire.

## FCC Information

**WARNING:** Changes or modifications to this equipment not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

**NOTE:** This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is needed.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation of device.

The manufacturer is not responsible for any radio or TV interference caused by unauthorized modifications to this equipment. Such modifications could void the user's authority to operate this equipment.

### **NOTICE TO DRIVERS IN CALIFORNIA AND MINNESOTA:**

State law prohibits drivers in California and Minnesota from using suction mounts on their windshields while operating motor vehicles. Other dashboard or friction mounting options should be used. PEAK® does not take any responsibility for any fines, penalties, or damages that may be incurred as a result of disregarding this notice. (See California Vehicle Code Section 26708(a); Minnesota Statutes 2005, Section 169.71)

## Limited Warranty

Manufacturer warrants to the original consumer, or purchaser, that the PEAK® Back-Up Camera System will be free from defects in material and workmanship for ninety (90) days from the date of sale to the original purchaser. Manufacturer hereby excludes and disclaims any and all other warranties, expressed or implied, beyond those warranties specified above. Manufacturer excludes any implied warranty of merchantability or fitness for a particular purpose.

IF YOUR PEAK® BACK-UP CAMERA SYSTEM MALFUNCTIONS DUE TO A DEFECT IN MATERIALS AND WORKMANSHIP WITHIN THE NINETY (90) DAY WARRANTY PERIOD, MANUFACTURER WILL, AT ITS ELECTION REPAIR OR REPLACE IT. MANUFACTURER SHALL NOT, HOWEVER, BE RESPONSIBLE FOR ANY DAMAGE TO YOUR PRODUCT DUE TO ANY CAUSE OTHER THAN DEFECTS IN MATERIAL OR WORKMANSHIP, INCLUDING WITHOUT LIMITATION: FAILURE TO FOLLOW INSTRUCTIONS FOR USE OR MISUSE, REPAIRS BY AN UNAUTHORIZED PERSON, MISHANDLING, MODIFICATIONS, NORMAL WEAR, ACCIDENT OR OVERLOAD, REPAIR OR REPLACEMENT AS PROVIDED UNDER THIS WARRANTY IS THE EXCLUSIVE REMEDY OF THE CONSUMER. MANUFACTURER SHALL NOT BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL OR PUNITIVE DAMAGES FOR BREACH OF ANY EXPRESSED OR IMPLIED WARRANTY ON THIS PRODUCT OR BASED ON ANY OTHER CAUSE OR CLAIM AGAINST MANUFACTURER.

### **To Obtain Service:**

1. **Before returning this product for any reason, please call toll free (800) 477-5847.**
  2. Do not return your PEAK® product to the place of purchase for service. Send your unit, postage prepaid and insured, along with a copy of the original sales receipt and a phone number to the address below. Pack your unit properly, as we are not responsible for any damage caused during shipping.
- PEAK® Electronics**  
**C/O Technical Services**  
**4065 Commercial Avenue**  
**Northbrook, IL 60062**
3. A copy of the original receipt is required for warranty service. If no receipt is provided, the unit manufacturer's date will be used as the date of purchase.



© PEAK® Products \* Northbrook, IL 60062 \* MADE IN CHINA