



Warrior, Inc.  
11100 SW Industrial Way  
Tualatin, Oregon 97062  
(503) 691-8915 Main  
(503) 692-0364 Fax  
(888) 220-6861 Toll Free  
[techsupport@warriorproducts.com](mailto:techsupport@warriorproducts.com)

---

**SUBJECT: INSTALLATION INSTRUCTIONS: 2360 License Plate Hawse Mount**

**Before Beginning:** This kit was built around a standard  $\frac{3}{4}$ " thick hawse. If your hawse is thicker or uniquely shaped you may not be able to use this bracket. It was also built with the intent to fit around a flat faced bumper opening.

1. Begin by unpacking your kit. You should find two different plates, two plastic handled knobs, and an assortment of bolts and nuts.
2. Begin by bolting your base plate (shaped similar to your aluminum hawse) behind the hawse on your bumper or winch plate. The two bent ears on the bracket should face forward on the top.
3. Slide your license plate over the 4 threaded studs on the license plate mount.
4. Affix a flat washer, external lock washer, and then an acorn nut to each stud to hold the license plate in place.
5. To install and uninstall your license plate. Hold the plate mount over ears on the mount now bolted to your bumper. Align the top two holes and secure with plastic handled knobs.

For more information on Warrior Products Jeep Parts and Accessories, please visit us on the web at  
[www.warriorproducts.com](http://www.warriorproducts.com)

