



www.DaystarWeb.com
Tech Support Contact Info
Tech@DaystarWeb.com
Phone: 623.907.0081
Fax: 623.907.0088
841 South 71st Avenue
Phoenix, AZ 85043

Greaseable Super Shackle kit. Part # KJ61017



Bill of Materials
S10315 X 2 TUBING S10191 X 4 1/2-13 BOLT S10190 X 2 1/2-13 NUT S10202 X 6 1/2-13 NUT S10748 X 2 COTTER PIN S10749 X 2 PIN CLEVIS S10740 X 4 SHACKLE SIDE PLATE M02203 X 8 BUSHINGS

Tools Needed
Jack stands Floor jack Wheel blocks Hand tools Hammer

CAUTION: BEFORE BEGINNING INSTALLATION, READ ALL INSTRUCTIONS CAREFULLY AND COMPLETELY.

1. Park vehicle on a level area and set the emergency brake. Block the tires opposite of the side you are working on. Lift one end of the vehicle using a floor jack until the wheel clears the ground approx 3". Place jack stands under the frame rail behind the spring perch. Lower vehicle onto the jack stands with the axle supported by the floor jack.
2. Carefully remove upper and lower spring mounting hardware, left and right shackles. Lower the axel carefully until the wheels touch the ground. Make sure that brake lines and the axel vent line is not over stretched.
3. Remove the spring eye bushings and steel sleeves assembly from spring eyes. Some frame shackle bushings need to reuse the outer spring shell. Take care not to damage the steel shell.
4. Lubricate the bushings before installing them.
5. Install the spring and frame shackle bushings and sleeves.
6. Install the shackle onto the frame side first. Shackles with off-centered tube, install the long end up toward the frame and short end down towards the spring.
7. Install the upper bolts and nuts. Tighten the nuts so the shackles swing freely. DO NOT OVER-TIGHTEN THE NUTS OR SHACKLE.
8. Using the floor jack raise the rear axle until the spring eye aligns with the shackle. Insert the bolts and tighten the nut. DO NOT OVER-TIGHTEN THE NUTS.
9. Grease the shackles bolts with **DAYSTAR LUBRETHANE POLY LUBE (KU11004)** or silicon and or Teflon lubricant.

WARNING

This vehicle has been modified to enhance its performance. The steering, braking and handling of this vehicle will differ from standard passenger cars and trucks. This vehicle handles differently from an ordinary vehicle in driving conditions which may occur on streets, highways and off road.

Avoid unnecessary abrupt maneuvers, sudden stops, sharp turns and other driving conditions that could cause loss of control, possibly leading to a roll over or other accident that could result in serious injury or death to driver and passengers. If larger tires are installed the speedometer will read lower than the vehicles actual speed.

DRIVE WITH CARE, REDUCE SPEED AND WEAR SEAT BELTS AT ALL TIMES.

This kit should be installed by a professional mechanic.



Instruction Sheet # P11184
2007 Daystar Products International Inc.