



## Rocker Guard Gasket

READ ALL OF THE INSTRUCTIONS BEFORE STARTING

### TOOLS REQUIRED

- Single Edge Razor Blade

NOTE: Gasket mounts on the Rocker Guard, not the JEEP® body.

Hold your Rocker Guard up to the JEEP® body and note all the areas it will make contact with the painted surfaces.

Place the Rocker Guard Gasket on your Rocker Guard and cut off any obvious excess.

Remove the adhesive backing paper and lightly install the Gasket, you will find it is easier to trim the Gasket to fit after installation, just run the razor blade around the edges of the metal to trim to size. Cut out all mounting holes. Firmly press Gasket in place. If you get an air bubble under the Gasket, just cut a slit in the center and press out the air.

Thank you for purchasing our product. We also manufacture many other body protection and accessory items for your vehicle, our complete product line can be viewed at [www.toughstuffproducts.com](http://www.toughstuffproducts.com).

---

©2003-2007 Tough Stuff Products, Inc. All rights reserved.

Jeep® and Wrangler™ are registered trademarks of DaimlerChrysler Corporation. Tough Stuff Products, Inc. has no affiliation with DaimlerChrysler Corporation. Firearm Security Vaults; Long Gun Security Vault; Handgun Security Vault; Crossmember Skid Plates; Paint, Door, Fender, Windshield Frame, Rocker Panel, Tailgate Sill, and Rear Corner Protectors; Tailgate Bump Guard; Rocker Guard Gasket; EZ-Flip; Hood Rack; Winch Safety Thimble; and GearNetz are trademarks of Tough Stuff Products, Inc. All rights reserved.