

There are Two (2) ways to install your new Center Hump Supreme Wedge

1. Velcro Strips to mount to your carpet - No Drilling Required
 - A) Peel and Stick The Hook Velcro to bottom of Wedge (rough portion)
 - B) Peel and stick the Loop Velcro to your center hump (soft portion)
 - C) Go to Step #7 for wiring procedures

OR

2. Two Mounting screws to drill through the wedge into the center hump.

Tools Required if mounted with screws:

- Razor Knife
- Wire Stripers
- Wire Cutters
- Electrical Tape
- Phillips Screwdriver
- Drill Motor



Jeep Installation



Truck Installation

- 1) Place the VDP Supreme Center Wedge on the center hump where you would like it. You will need to cut a small slit in the carpet behind the Supreme Wedge where the wire hole is. (To run wire up to dash)
- 2) Set the Supreme Wedge just to the side. Run the Speaker and Power wires through the slit in carpet and run them up and under the dash. **DO NOT HOOK UP YET** (See Step 6. for speaker and power hook up)
- 3) Connect the wire harness to the back of the Wedge
- 4) Center Wedge Installation:
 - 1) Remove both Speaker grills - using a small pin or paper clip (**Fig. 1**)
 - 2) Remove the (4) four screws holding the Speaker and LED Light Ring (**Fig. 2**)
 - 3) Remove the speakers and LED light ring carefully and lay right next to the wedge housing. (**Fig. 3**)
(NOTE: YOU DO NOT NEED TO DISCONNECT THE INTERNAL WIRES TO SPEAKER OR LIGHT RING)
- 5) With the Speakers and LED light ring removed - But wires still connected - Place the Supreme Wedge back into place on the vehicles center hump.
- 6) With the Wedge in place - Drill (2) 3/16" Holes (One in each speaker opening) use screws provided to mount through the bottom of the wedge into center hump (**Fig. 4**)
IMPORTANT NOTE: Drill hole into the center area of each speaker.
- 7) Screw the Speakers and the LED light ring back into the Supreme Center Wedge and Replace grills. (**Fig. 5**)
- 8) Connecting Speakers:
Splice wires from the Wedge into the left and right speaker wires under the dash

Drivers Side - Left	Passenger Side - Right
Green / Red (+)	White /Red (+)
Green (-)	White (-)
- 9) Connecting the Power for the LED Light Show
LED Light Show
Red (+) Attach to Battery or Fuse
Black(-) Attach to a good ground



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5

Vertically Driven Products
1401 Freeman Avenue
Long Beach, CA 90804
(562) 438-5112
info@vdpusa.com