



PREPARING: Clean filter prior to oiling. Gently tap the filter to remove excess dirt. Lightly brush off surface dirt with soft bristle brush. Agitate element in ½" of hot water and laundry detergent, dishwashing soap, or an industrial cleaner (NONFLAMMABLE). DO NOT USE GAS OR FLAMMABLE LIQUIDS.


SOAKING: (Fig. A)
Spray the filter media with the Volant air filter cleaning agent (Part No. #VFC-101) until thoroughly soaked. Let the filter soak for approximately 10 minutes.



RINSING: (Fig. B)
Using low pressure from a tap or hose, rinse the element from the inside out until the water flows clear. DO NOT USE HIGH PRESSURE NOSELS NOR HOSES. Air dry naturally or lay the filter in front of a fan using a low setting. DO NOT USE HEAT NOR HIGH PRESSURE AIR AS IT CAN DAMAGE THE MEDIA.



OILING: (Fig. C)
Before using Volant's special formula aerosol air filter oil (Part No. #VCOB-101), check to see if the filter media is completely dry. Hold can 4" away and make only one pass around the element. Let element stand for 20 minutes so the oil can be soaked up by the dry areas. This process allows the oil to wick throughout the filter media. If light spots appear spot touch those areas. NEVER USE A VOLANT FILTER WITHOUT OIL.



AIR FILTER CLEANER

CAUTION: MAY BE HARMFUL IF SWALLOWED. AVOID PROLONGED CONTACT WITH SKIN AND EYES. KEEP OUT OF REACH OF CHILDREN. CALL PHYSICIAN IMMEDIATELY.

PART NO. #VFC-101
12 FL. OZ. / 0.355 LITERS

NOTE: Sunlight deteriorates the oil. If the filter is exposed to sunlight for extended periods of time it will be necessary to re-oil the filter periodically.

**DO NOT USE COMPRESSED AIR
DO NOT USE OPEN FLAME
DO NOT USE HOT AIR DRYERS
DO NOT USE GASOLINE OR OTHER CAUSTIC CLEANING SOLUTIONS.**

CAUTION:
Avoid contact with skin, eyes and mucous membranes.

FIRST AID:
Eye Contact:
Flush with water for 15 minutes. If irritation persists call physician.
Inhalation:
Remove to fresh air. If breathing is difficult, get medical attention.
Ingestion:
Do not induce vomiting. Drink 1 to 2 large glasses of water followed by citrus juice. Call physician.

MADE IN THE USA

Technical Support
(909) 476-7225 BUS
(909) 476-1491 FAX
Volant Cool Air Intakes
9400 7th St. Unit C-1
Rancho Cucamonga, CA 91730
www.volantperformance.com

PREPARING AND CLEANING

CLEANING (WET): Remove clinging debris from element by gently tapping on a hard surface. Lightly brush heavily soiled areas. Agitate element in ½" of hot water and laundry detergent, dishwashing soap, or an industrial cleaner (NONFLAMMABLE). DO NOT USE GAS OR FLAMMABLE LIQUIDS. Spray the filter media with the Volant air filter cleaning agent (Part No. #VFC-101) until thoroughly soaked. Let the filter soak for approximately 10 minutes. Using low pressure from a tap or hose, rinse the element from the inside out until the water flows clear. DO NOT USE HIGH PRESSURE NOSELS NOR HOSES. Air dry naturally or lay the filter in front of a fan using a low setting. Element can then be re-oiled and left to dry. A very light oiling is recommended after each washing. DO NOT USE HEAT NOR HIGH PRESSURE AIR AS IT CAN DAMAGE THE MEDIA.

OILING

Before using Volant's special formula aerosol air filter oil (Part No. #VCOB-101), check to see if the filter media is completely dry. Hold can 4" away and make only one pass around the element. Let element stand for 20 minutes so the oil can be soaked up by the dry areas. The oil should completely cover all pleats without dripping from the element edges. This process allows the oil to wick throughout the filter media. If light spots appear spot touch those areas. NEVER USE A VOLANT FILTER WITHOUT OIL.

Important Notice to Purchaser: The following warranty is in lieu of all other expressed or implied warranty, namely that the product is manufactured with first-class materials and under the most rigid scientific quality controls. The liability of the manufacturer and/or distributor shall not exceed the purchase price of this can. Manufacturer and/or vendor assumes no responsibility, express or implied, for results of misuse or misapplication, or for any injury that might be sustained through ingestion, inhalation, or absorption through any body surface.

READ PRECAUTIONS CAREFULLY BEFORE USING THIS PRODUCT

DANGER: EXTREMELY FLAMMABLE. Do not spray into or use near sparks, open flame nor pilot light. Vapors will accumulate and may ignite explosively. Keep area well ventilated during use and until all vapors are gone. **HARMFUL OR FATAL IF SWALLOWED.** Do not ingest, eat nor swallow. **EYE IRRITANT:** Avoid contact with eyes or skin. **VAPOR HARMFUL:** Contains Petroleum Distillates. Avoid inhalation of vapors. Use with adequate ventilation. Avoid continuous breathing of vapor or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air or wear respirator protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. **CONTENTS UNDER PRESSURE:** Do not puncture, incinerate, burn nor store above 120° F. Do not set on stove nor radiator. Do not discard empty into home trash compactor. **FIRST AID:** If swallowed, immediately give 1 or 2 glasses of water. Call physician, hospital emergency room, or Poison Control Center immediately for instructions to induce vomiting. When medical advice is not available, induce vomiting using syrup of Ipecac according to directions. If Ipecac is unavailable, induce vomiting with finger or back of spoon. Get prompt medical attention. In case of eye contact, flush thoroughly with copious amounts of water for 15 minutes and get medical attention. For skin contact wash thoroughly with soap and water. In case of respiration difficulty, provide fresh air and call physician. **INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL AND IN SOME CASES FATAL.**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

KEEP OUT OF REACH OF CHILDREN

WARRANTY STATEMENT: This warranty is in lieu of all other expressed or implied warranty. This product is manufactured with the highest quality material and under the most rigid scientific quality controls. Manufacturer and/or sellers cannot control the use of this product. Therefore, the liability of the manufacturer and/or sellers shall not exceed the purchase price of can.

TECHNICAL SUPPORT

Volant Cool Air Intakes 9400 7th St. Unit C-1 Rancho Cucamonga, CA 91730
(909) 476-7225 BUS (909) 476-1491 FAX
www.volantperformance.com
MADE IN THE USA



AIR FILTER OIL AEROSOL SPRAY FOR ALL FABRIC FILTERS

**COLOR
BLUE**

**DANGER: EXTREMELY FLAMMABLE
HARMFUL OR FATAL IF SWALLOWED.
EYE IRRITANT. VAPOR HARMFUL
CONTENTS UNDER PRESSURE
(Read Other Precautions on Back**

PART NO. #VFOB-101
NET WT 12.3 OZ. / 0.364 LITERS