

THE ROCK

If your Jeep® Vehicle is equipped with the optional Sentry Key® theft-deterrent system, you'll need to program your vehicle to accept your new "The Rock" key. After having your new key cut at your local Jeep® dealership or local hardware store, follow the instructions below to program your vehicle to accept the key.

ON-BOARD PROGRAMMING INSTRUCTIONS

IMPORTANT: READ INSTRUCTIONS ENTIRELY BEFORE STARTING THE PROGRAMMING PROCESS.

Add Duplicate Key (**Requires Two Original Keys**)

1. Insert one of the two original keys into the ignition and turn to the ON (but not START) position. All of the lights on the dash will illuminate.
2. Turn the key to OFF after 5 seconds, but no more than 15 seconds.
3. Remove that key and insert the second valid key and turn it to the ON (but not START) position within 15 seconds. (The second key must NOT be the same as the first key.)
4. A security light should illuminate after ten seconds and a single chime will indicate entry into the vehicle's immobilizer.
5. Turn the second valid key to OFF and remove it within 60 seconds.
6. Insert the new key into the ignition and turn it to the ON (but not START) position.
7. After approximately 10-15 seconds, a single chime will sound and the theft alarm light will stop. Wait three seconds and turn to the OFF position. Your "ROCK" key is now programmed.

* Transponder equipped vehicles with only one original key must see a local dealer or locksmith for key programming.