

INSTALLATION INSTRUCTIONS

PART No. FB23008, FB23009

**Jeep® JK Wrangler
Rocker Guards – 2DR & 4DR**



FB23008 – 2DR



FB23009 – 4DR



FB23009 shown



VIDEO AVAILABLE

REQUIRED TOOLS

16mm Socket &
Extension

KIT CONTAINS

Rocker Guard – Left
Rocker Guard – Right

QTY

1
1

- 1) REMOVE FACTORY RAILS/GUARDS**
Remove the factory equipment if equipped.

- 2) INSTALL ROCKER GUARDS**
Using a 16mm socket, remove the nuts on either side of the body mount bolts. Complete this step on both the front and rear brackets.

Identify the driver and passenger side. The front of the rocker guard is welded in the center of the bracket as seen below. The rears are welded off-center of the bracket.





INSTALLATION INSTRUCTIONS

PART No. FB23008, FB23009

**Jeep® JK Wrangler
Rocker Guards – 2DR & 4DR**

NOTE

The use of a floor jack to lift the rocker guard into position can help if you do not have someone to help hold it in place.

Install the rocker guard by lifting it into position over the body studs. Reusing the OEM nuts, secure the rocker guard in place.



- 3) **HIT THE TRAILS AND ENJOY YOUR NEW ROCKER GUARDS!**