



INSTALLATION INSTRUCTIONS

PART No.

FB23209R

**Jeep® JT Gladiator
JT Rear Steel Tube Fenders**



REQUIRED TOOLS

5mm Allen

Note: These instructions will **NOT** cover how to remove factory fenders or inner fenders, and will **NOT** cover how to install inner fenders. Instructions on how to do so are available on www.FishboneOffroad.com , or www.FishboneOffroad.tv .

KIT CONTAINS

Rear Fender (Left & Right)
Rubber Seal
M8 Button Head Bolt
M8 Flat Washer
M8 Serrated Nut

QTY

2
2
18
18
18

23209R00

Jeep® JT Gladiator JT Rear Steel Tube Fenders

1) REMOVE

Begin by removing any inner and outer fenders your vehicle currently has installed.

2) PREPARE

The included rubber seals are driver and passenger side specific. Identify which side which is which by the bolt hole indents in the rubber. Peel off the backing and carefully apply the seal to the vehicle side wall of each fender.



3) INSTALL REAR FENDERS

Hold the corresponding fender up to the body and begin loosely securing it with 9 of the included M8 bolts, 9 washers, and 9 serrated nuts.



With a 5mm Allen key, tighten down the bolts.



Repeat on the opposite side.

4) ENJOY YOUR NEW FISHBONE OFFROAD REAR JT FENDERS

