

This product can expose you to chemicals including vinyl chloride and lead, which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

The Kicker Speakers were shipped with Kicker Grills in the Box. They are not need for this installation.

They are included in the Box to protect the Speakers during shipping.

- 1. Remove the Glove Box by squeezing the two sides together at the top as shown in picture #1.
- 2. Using a small flat edge or trim tool, remove the Passenger Side Dash Panel as shown in picture #2.
- 3. Using a 7mm socket, remove the Two Screws from the Passenger Side Speaker Box as shown in picture #3.
- 4. Using a 10mm socket, remove the Dash Bolt as shown in picture #4.
- 5. Unplug the Speaker Wires as shown in picture #5.
- 6. Gently slide the Speaker Box toward the Glove Box opening until you gain access to the Speaker.

At this point you can choose to either remove the box from the Dash or you can leave the Speaker in the Glove Box opening and work on it from there.

- 7. Remove the Three Screws holding the Speaker in. Unplug the old speaker and plug in the New Speaker. Pay attention to the Three Tabs on the Speaker. The Tab at the Top of the Speaker Box is the Long Tab. Make sure you install the Long Tab on the New Speaker facing up, the same way the original came out.
- 8. Reassemble the Passenger Side Dash.











