



STEP-BY-STEP INSTRUCTION MANUAL

JEEP WRANGLER - JK 2015 & ABOVE

SOUNDBAR XL INSTALLATION

VERSION 12/12/2016

FOR QUESTIONS OR CLARIFICATIONS, PLEASE EMAIL: SUPPORT@KISPRODUCTS.COM

1. Safety Precautions

While the KIS SOUNDBAR XL is a simple 7 minute install; safety is the most important factor with any removal or installation process. Thus, it is highly recommended that 2 people complete this install.

During the removal and installation, anyone removing screws should wear safety goggles.

During the removal and installation, make sure that the vehicle is turned off, in park, on a level surface, and that the key is out of the ignition.

2. Required Tools & Equipment

Find a friend who can hold one side of the soundbar for a few minutes.

Tools Required:

- Socket Wrench
- 10mm Socket
- Safety Glasses

3. Handling, Care & Cleaning

Always handle the sound bar with care and do not drop.

When placing on a table, always have the speaker side facing up, and laying on a level clean surface.

Never expose your KIS Soundbar XL to submersed water or chemicals of any kind.

To clean the acrylic face plates, use a microfiber cloth that may be damped with water ONLY,

Never place extra weight on the sound bar, and never use it as a grab handle or a tie down area.

4. INSTALLATION PREVIEW:

As desired, before installation, you can also watch the installation video at www.jeepsoundbar.com

For any issues during installation; please call KIS' office at 972.331.4100 and we'll immediately help.

5. OEM Sound Bar Removal

Step 1: Locate the 6 - 10mm Bolts that hold the OEM Sound Bar into place.



Step 2: Starting on the passenger side, remove the 2 - 10mm bolts that hold the sound bar to the roll cage, and also the one in the middle of the sound bar closest to the passenger side.



Step 3: Allow the passenger side of the sound bar to hang down so that you can unplug the connector. A trick here is pressing the “release clip” on the plug for a quick and easy removal.



Step 4: After unplugging the connector on the passenger side, remove the remaining 10mm bolts on the driver side of the vehicle, and remove the sound bar.



6. KIS Sound Bar Installation

Step 1: With help of a second person, raise and hold the KIS Sound Bar into the same location & position as the OEM sound bar was previously located/positioned.



Step 2: Connect the plug on the passenger side of the sound bar.



Step 3: Start all 6 bolts by hand, and then tighten to secure the sound bar to the top of the vehicle.



Step 4: Adjust the "Fade" on your radio more to the middle of your vehicle so you can maximize the sound coming from your new high performance speakers. Enjoy your new KIS Jeep JK Sound Bar!

