

Installation Manual for '18 -Current Wrangler JL / Gladiator JT Vehicles With Active Cruise Control (ACC) #97109-1138









AWARNING A

TO REDUCE RISK OF SERIOUS INJURY OR PROPERTY DAMAGE: READ ALL SAFETY MESSAGES AND UNDERSTAND ALL INSTRUCTIONS AND PROCEDURE NOTICES BEFORE ATTEMPTING TO INSTALL OR USE THIS PRODUCT.

ACAUTION A

RISK OF EYE INJURY! SAFETY GLASSES MUST BE WORN AT ALL TIMES WHILE INSTALLING OR MAINTAINING THIS PRODUCT. DO NOT USE IF DAMAGED.

NOTICE

CHECK STATE AND LOCAL HIGHWAY SAFETY LAWS REGARDING USE OF AUXILLARY LIGHTING.

THESE ARE INTENDED FOR OFF ROAD USE ONLY.

ACAUTION A

WHEN ROUTING ELECTRICAL WIRES, ALWAYS AVOID PINCHING WIRES. ALWAYS AVOID HOT OR MOVING COMPONENTS. ALWAYS SECURE WIRES WITH CABLE TIES.

AWARNING A

HOT SURFACE! DO NOT TOUCH LIGHT HOUSING WHILE IN OPERATION.



A Few Words About Product Safety: Your Stealth LED Lightbar is designed to enhance the utility and enjoyment of your off road capable vehicle. Before installation, please take a moment to review the following safety information and installation Instructions.

Important safety information is generally preceded by one of three signal words indicating the relative risk of injury. The signal words mean:

AWARNING A

A hazardous situation which, if not avoided, could result in death or serious injury. You CAN be KILLED or SERIOUSLY HURT if you don't follow instructions.

ACAUTION A

A hazardous situation which, if not avoided, could result in minor or moderate injury. You CAN be moderately HURT and also may suffer property damage if you don't follow instructions.

NOTICE

Careful attention is required to this instruction or operation but does generally not relate to personal injury. Damage to your Quadratec® product or other property may result if you don't follow instructions.

Before You Begin Installation: Congratulations on your purchase of the Stealth LED Lightbar for your Jeep® Wrangler. When unpacking, check to make sure all parts are included and not damaged due

to shipping. If any part is missing or broken, please call Customer Service at 800-745-6037 as soon as possible.

Thank you again for your purchase and let's start the installation process.

ACAUTION A

READ ALL SAFETY MESSAGES AND ALWAYS WEAR SAFETY GLASSES WHEN WORKING WITH TOOLS.

NOTICE

THE LIGHTBAR IS SOMEWHAT AWKWARD TO HANDLE DURING INSTALLATION. WE RECOMMEND GETTING ASSISTANCE TO PREVENT DAMAGE TO THE PRODUCT OR YOUR VEHICLE.

ACAUTION A

WHEN ROUTING ELECTRICAL WIRES, ALWAYS AVOID PINCHING WIRES. ALWAYS AVOID HOT OR MOVING COMPONENTS. SECURE WIRES WITH CABLE TIES.


NOTICE

THIS PRODUCT IS COMPATIBLE WITH MANUAL REAR VIEW MIRROR AND WITH THE FACTORY AUTO-DIMMING REAR VIEW MIRROR.

THIS PRODUCT IS NOT COMPATIBLE WITH VEHICLES EQUIPPED WITH ADAPTIVE CRUISE CONTROL (ACC) FROM THE FACTORY



Quadratec Stealth Light Bar Parts & Tools:



PARTS LIST:

A)	Light Bar	QTY 1
B)	Left Mounting Bracket	QTY 1
C)	Right Mounting Bracket	QTY 1
D)	Torx Screws/washers	QTY 8
E)	Cross Brace	QTY 1
F)	Power Tap Harness	QTY 1
G)	Cable Ties	QTY 4
H)	Light Power Cord	QTY 1

REQUIRED TOOLS:

Safety Glasses
Forked Clip/Trim Removal Tool
Stubby Phillips Head Screwdriver
Small Flat Head Screwdriver
7MM Socket (1/4" drive)
10mm Socket (1/4" drive)
1/4" Ratchet
T-40 Socket & Extension Side Cutters

LED Lightbar Installation:



Put on safety glasses. Using a trim clip removal tool gently remove the center dash control center (FIG 1)



Disconnect any wiring harnesses and set control panel aside. (FIG 2)


NOTE: For 2023 and older models skip to figure 11 page 6.



FIG3 - FIG10 ARE FOR 2024 AND NEWER WRANGLERS AND GLADIATORS ONLY. IF YOUR VEHICLE IS 2023 OR EARLIER THEN PLEASE PROCEED TO FIG11.



Pop off passenger side cover plate using trim removal tool as shown. (FIG 3)



Using a 7mm socket or stubby Phillips head screwdriver remove side grab handle mounting screws. (FIG 4)



Using trim removal tool gently pry the top trim cover up and out to expose top two grab handle mounting screws. (FIG 5)



Remove top two grab handle mounting screws using the 7mm socket and ratchet. (FIG 6)



Using trim removal tool pop off screw access panel located on back side of grab handle just in front of glove box. (FIG 7)



Using the 7mm socket and ratchet remove the three rear facing Phillips head screws. (FIG 8)



LED Lightbar Installation (2024 - current):





Using trim removal tool gently pry grab handle trim cover and center dash control center away from console. (FIG 9A and 9B)



Disconnect any wiring harnesses and set control panel aside . (FIG 10)

This is the end of 2024 only instructions. Continue to Page 6.






Remove the center screw using a Phillips head screwdriver and set aside.(FIG 11)



Gently pry out the window control panel from the top and work your way down. (FIG 12)



Tilt panel away enough to access the 12v socket connection. Squeeze the blue tab and disconnect it. (FIG 13)



Connect new Power Tap Harness white connector to the plug you just disconnected in FIG14. Re-connect the new Power Tap gray connector back into the 12v socket. (FIG 13)



Open the glove box and disconnect the strut on the side by sliding it towards the top of the glove box. (FIG 15)





Push up on the glove box stop, tilt glovebox down, remove it and set aside.(FIG16) Now, route the Power Tap Harness through the dash and out behind the the glove box.



(FIG 17) You may now replace all of the center dash parts in the reverse order of removal.


Do not re-install the glove box yet.



Using a trim tool gently pry up on the dash speaker cover and remove it. (FIG 18)



Using a trim tool gently remove the Apillar grab handle covers. (FIG 19)



Remove the two bolts using a 10mm socket. (FIG 20) Remove handle and set it aside.





Unlatch and open the soft top or remove hard top front panels. Remove the felt padding on top of the brackets hardware. (FIG 21)



Remove the hardware using a T-40 Torx socket and loosely install the supplied brackets as shown. (FIG 22)

NOTICE

NOTE THAT THE BRACKET IS NOT SYMMETRIC. THE SLOTS ON THE BRACKETS ARE 2 DIFFERENT SIZES. THE LARGER HOLES MUST BE USED ON THE TOP.



Tilt the driver side light bar into place. (FIG 23) Loosely attach the light bar to the bracket using the supplied T-40 torx bolts. Next, route the passenger side light bar up and over rear



view mirror. Connect light bar power cord to light. Loosely attach the light bar to the bracket using the supplied T-40 torx bolts. (FIG 24). NOTE: For 2024 and newer JLs and JTs ensure housing clears windshield antenna connector.



Now, route light power cord as shown down the A-pillar along side of the factory wiring. (FIG 25)



Fish the light bar power harness down through the dash to behind the glove box. (FIG 26)



Using a small flat blade screwdriver connect the light bar's power cord to the power tap harness. (FIG 27) You may now re-install the glove box in the reverse order.



Re-install the grab handle taking care not to pinch any wires. (FIG 28)

Also, re-install the speaker cover.



Now push the light brackets forward until they rest against the plastic trim. (FIG 29) You may now tighten the factory T-40 screws. Some adjustment may be necessary to re-align the brackets to your top latches.



Finally, push up on the light bar and tighten the T-40 screws from bracket to light bar. (FIG 30). NOTE: Final adjustment of light bar will be required to ensure light is not bleeding past seals.

NOTE: DO NOT exceed 25 ft. lbs of torque. Installation is now complete.



With the light bar finally in place, install the cross brace using the supplied T-40 torx bolts. Use provided cable ties to at-tach wire to cross brace and cut excess cable tie with side cutters.



Observe location of the 3 Position Switch (switch position may vary). See above for the various settings based on rocker switch position.



Lifetime Limited Warranty

Your Quadratec® branded accessories are covered by the following **Limited Warranty** provided exclusively by Quadratec, Inc., 1028 Saunders Lane, West Chester PA 19380.

This Limited Warranty is the only warranty made in connection with your purchase. Quadratec neither assumes nor authorizes any vendor, retailer or other person or entity to assume for it any other obligation or liability in connection with this product or Limited Warranty. This Limited Warranty does not apply and is not cumulative to any accessory or part distributed by Quadratec for which the Manufacturer provides a separate written warranty.

What is Covered: Subject to the terms, exclusions and limitations herein and with respect only to Quadratec branded accessories first sold in the United States. Quadratec warrants Off-Road LED Light Bars, LED Auxiliary Lights, LED Work Utility Lights to be free of original defects in material and workmanship to the original purchaser of the product, with proof of purchase, and is limited to the original vehicle installation. Quadratec will repair or replace, at its sole discretion. product covered by this warranty. If, at our discretion a product requires repair or return, the customer (end consumer) will be responsible for the cost of shipping to and from the manufacturer as needed. Standard shipping for claims is ground to and from manufacturer. Any expedited shipping fees will be incurred at the discretion of the consumer.

This **Limited Warranty** is not assignable and shall terminate upon sale of the vehicle upon which the Quadratec accessory is installed or other transfer third persons.

All other warranties are hereby disclaimed, except to the extent prohibited by applicable law in which case any implied warranty of merchantability or fitness for a particular purpose on this product is limited to 3 year from date of initial retail sale. Quadratec reserves the rights to: (a.) require invoice or other proof your accessory is within the terms of this **Limited Warranty** as a condition of warranty service and, (b.) make future revisions to this product and **Limited Warranty** without prior notice or obligation to upgrade your product.

What is Not Covered:

Your Quadratec Limited Warranty does not cover products or parts Quadratec determines to have been damaged by or subjected to: (a.) installation damage, alteration, modification, combination with other parts, failure to maintain or improper repair or service, (b.) normal wear & tear, cosmetic damage or damage from moisture or water immersion, (c.) Acts of God, accidents, misuse, negligence, inadequate mounting or impact with vehicle(s), obstacles or other aspects of the environment, (d.) theft, vandalism or other intentional damage.

This warranty is void if the LED housing is opened or unscrewed, if the protective seal is broken, or if tampering is evident. Quadratec reserves the right to make the aforementioned determinations to grant or deny warranty. Quadratec shall have no liability for any incidental or consequential damages of any kind including property damage, or personal injury resulting from the use or misuse of this product. Warranty excludes LED Brackets.

Remedy Limited to Repair/Replacement: The exclusive remedy provided hereundershall, upon Quadratecin-spection and at Quadratec's option, be either repair or replacement of product or parts (new or refurbished) covered under this Limited Warranty. Customers requesting warranty consideration should first contact Quadratec to obtain a RGA number (610-701-3336). All labor, removal, shipping and installation costs are customer's responsibility.

Other Limitations - Exclusion of Damages - Your Rights Under State Law: In consideration of the purchase price paid, neither Quadratec nor any independent Quadratec distributor/licensee are responsible for any time loss, rental costs, or for any incidental, consequential, punitive or other damages you may have or incur in connection with any part or product purchased. Your exclusive remedy hereunder for covered parts is repair/replacement as described above.

This Limited Warranty gives you specific rights. You may also have other rights that vary from state to state. For example, some states do not allow limitations of how long an implied warranty lasts and /or do not allow the exclusion or limitation of incidental or consequential damages, so the limitations and exclusions herein may not apply to you.

©Quadratec, Inc. 2024. All Rights Reserved. LTR Version 6.26.20

Instructions Part #12999.3145

