Quadratec® Aluminum Billet Locking Fuel Door

Installation Manual: for '07-'18 Jeep Wranglers (JK) #15001-3001



KIT CONTENT LIST: Fuel Door and Housing Keys (2) Plastic Fuel Bay Door Liner Anchoring Bolts REQUIRED TOOLS: Safety Glasses Phillips Head Screwdriver Torque Wrench with 4mm Hex Bit



A FEW WORDS ABOUT PRODUCT SAFETY:

Your Quadratec Jeep protection product is intended to enhance the utility and enjoyment of your off road capable vehicle. Follow safety information and installation recommendations. Throughout these instructions is important safety information that is generally preceded by one of three signal words indicating the relative risk of injury, property damage or adverse consequence.

The signal words mean:



A HAZARDOUS SITUATION WHICH, IF NOT AVOIDED, COULD RESULT IN DEATH OR SERIOUS INJURY. YOU CAN BE KILLED OR SERIOUSLY HURT IF YOU DON'T FOLLOW INSTRUCTIONS



A HAZARDOUS SITUATION WHICH, IF NOT AVOIDED, COULD RESULT IN A MINOR OR MODERATE INJURY. YOU CAN BE MODERATELY HURT AND ALSO MAY SUFFER PROPERTY DAMAGE IF YOU DON'T FOLLOW INSTRUCTIONS.

NOTICE

CAREFUL ATTENTION IS REQUIRED TO THIS INSTRUCTION OR OPERATION BUT DOES GENERALLY NOT RELATE TO PERSONAL INJURY. DAMAGE TO YOUR QUADRATEC® PRODUCT OR OTHER PROPERTY MAY RESULT IF YOU DON'T FOLLOW INSTRUCTIONS.

BEFORE YOU BEGIN INSTALLATION:

Congratulations on your purchase of Quadratec® *product* for your Jeep® Wrangler. This custom *product* has been designed for protection, long life, and great looks. When unpacking, check to make sure all parts are included and not damaged due to shipping. If any part is missing or broken, please call Customer Service at 800-745-6037 as soon as possible. Thank you again for your purchase and let's start the installation process.



TO REDUCE RISK OF SERIOUS INJURY OR PROPERTY DAMAGE: READ ALL SAFETY MESSAGES AND UNDERSTAND ALL INSTRUCTIONS AND PROCEDURE NOTICES BEFORE ATTEMPTING TO INSTALL OR USE THIS PRODUCT.




READ ALL SAFETY MESSAGES AND ALWAYS WEAR SAFETY GLASSES WHEN WORKING WITH TOOLS.



STEP 1- '07 - '18 JK INSTALLATION





Put on safety glasses.Locate the rear driver's side tail light housing. Using a Phillips Head Screw driver, remove the two screws on the right corners of housing. (Fig 1) With a good grasp on the tail light housing, slide housing right and pull away from body of the Jeep. Locate the wiring harness that attaches the light to the other cable. While pressing the tab on the gray connector, gently pull the parts of the harness apart. You can now set the signal light housing aside until reassembly. (Fig 2)


STEP 2





Locate gas cap. Thoroughly clean the area around the gas cap before removing. Remove gas cap. (Fig 3) Carefully remove retaining cord by sliding your thumb under the elongated portion of the cable that is attached to the plastic inner liner. Using your finger and thumb to hold the retaining line, pry the clip out of the hole. Set the gas cap aside until reassembly. (Fig 4)

STEP 3





Placing your hand through the opening left from removing the tail light, locate two of the push tabs on the closest side of the gas cap liner. (Fig 5) While slightly pulling on the outside of the liner, press the tabs releasing the liner. (Fig 6) Once those tabs are free slide the liner to the right to free the other two tabs.



STEP 4






Carefully pull the liner with rubber grommet away from the filler neck. Remove and retain the rubber grommet to be placed onto the new plastic liner. (Fig 7) Work rubber grommet onto new inner plastic liner. (Fig 8) The rim of the hole in the liner should completely fill the groove in the rubber grommet.

STEP 5





Carefully work rubber grommet and liner around the gas filler neck, while keeping the larger opening on the new inner liner to the left. (Fig 9) It might be helpful to reach through the tail light opening and hold the filler neck securely while seating the rubber grommet. Make sure all 4 clips on the new inner liner are engaged and hold the liner in place. (Fig 10)

STEP 6






Take new filler door and align the four openings for the hex bolts with the four captured nuts in the liner. Note that the hinge of the fuel door should fit into the larger opening on the left of the liner. (Fig 11) Using a small torque wrench with a 4mm hex bit, tighten the bolts to no more than 15 inch lbs of torque. Do not overtighten. (Fig 12)

STEP 7





Locate the small hole on the left side of the liner and insert the retaining clip for the gas cap until it clips into place. (Fig13) Replace gas cap back into the filler neck and secure. Close fuel door to test fit. (Fig 14) Reconnect the wiring harness and align tail light back on the vehicle. Locate the two tabs on the back of the light housing. Sliding those tabs behind the metal on the left slide of the opening and slide the housing left. Reattach tail light housing with two original screws and tighten securely. Do not over tighten.

STEP 8



Note: On the 4 door, there is a tab on the back of the new inner liner that will fit in the hole next to the edge of the opening in the metal. If Fuel Door will be installed on a 2 door, use a pair of cutters to remove that tab since there is no hole in the metal on the Jeep. (Fig15)

Quadratec® Exclusive Three Year Limited Warranty

Your Quadratec® branded accessories are covered by the following Limited Warranty provided exclusively by Quadratec, Inc., 1028 Saunders Lane, West Chester PA 19380.

This **Limited Warranty** is the only warranty made in connection with your purchase. Quadratec neither assumes nor authorizes any vendor, retailer or other person or entity to assume for it any other obligation or liability in connection with this product or Limited Warranty. This Limited Warranty does not apply and is not cumulative to any accessory or part distributed by Quadratec for which the Manufacturer provides a separate written warranty.

What is Covered:

Subject to the terms, exclusions and limitations herein and with respect only to Quadratec branded accessories first sold in the United States, Quadratec warrants to the initial retail purchaser only that your Quadratec accessory shall be free of defects in material and workmanship: for a period of three (3) years from date of retail purchase.

This **Limited Warranty** is not assignable and shall terminate upon sale of the vehicle upon which the Quadratec accessory is installed or other transfer to third persons.

All other warranties are hereby disclaimed, except to the extent prohibited by applicable law in which case any implied warranty of merchantability or fitness for a particular purpose on this product is limited to three (3) years from date of initial retail sale. Quadratec reserves the rights to: (a.) require invoice or other proof your accessory is within the terms of this Limited Warranty as a condition of warranty service and, (b.) make future revisions to this product and Limited Warranty without prior notice or obligation to upgrade your product.

What is Not Covered:

Your Quadratec Limited Warranty does not cover products or parts Quadratec determines to have been damaged by or subjected to: (a.) installation damage, alteration, modification, combination with other parts, failure to maintain or improper repair or service, (b.) normal wear & tear, cosmetic damage or damage from moisture or water immersion, (c.) Acts of God, accidents, misuse, negligence, inadequate mounting or impact with vehicle(s), obstacles or other aspects of the environment, (d.) theft, vandalism or other intentional damage.

Remedy Limited to Repair/Replacement:

The exclusive remedy provided hereunder shall, upon Quadratec inspection and at our option, be either repair or replacement of product or parts (new or refurbished) covered under this Limited Warranty. Customers requesting warranty consideration should first contact Quadratec to obtain a RGA number (610-701-3336). All labor, removal, shipping and installation costs are customer's responsibility.

Other Limitations - Exclusion of Damages - Your Rights Under State Law:

In consideration of the purchase price paid, neither Quadratec nor any independent Quadratec distributor/licensee are responsible for any time loss, rental costs, or for any incidental, consequential, punitive or other damages you may have or incur in connection with any part or product purchased. Your exclusive remedy hereunder for covered parts is repair/replacement as described above.

This **Limited Warranty** gives you specific rights. You may also have other rights that vary from state to state. For example, some states do not allow limitations of how long an implied warranty lasts and /or do not allow the exclusion or limitation of incidental or consequential damages, so the limitations and exclusions herein may not apply to you.

©Quadratec, Inc. 2025. All Rights Reserved. A4 Version 8.29.2025

Instructions Part #12999.31777

