

ROCK HARD 4X4 JEEP WRANGLER JK 2/4-DOOR 2007-2017 WINCH PLATE FOR OEM PLASTIC FRONT BUMPER PART #: RH-5010 Installation Manual



INSTALLATION VIDEO AVAILABLE



PLEASE VISIT YOUTUBE.COM/C/ROCKHARD4X4

PACKING LIST:

- **1- WINCH PLATE**
- 2 ¹/₂" X 13 X 1" GRADE 5 HEX BOLT
- 2 $\frac{1}{2}$ " SAE WASHER
- 2 ¹/₂" LOCK WASHER

REQUIRED TOOLS:

18MM SOCKET 3" EXTENSION 3/4" SOCKET

Thank you for your purchase! Whether you bought this Rock Hard 4x4 product from one of our fantastic dealers or our factory direct team, we thank you for your business.

Rock Hard 4x4 is a family owned and operated business. We are headquartered in Saint Paul, Nebraska where we design, fabricate, and produce every single one of our products. Every single part we manufacture is 100% Made in the USA and exclusively in house by the Rock Hard 4x4 team.

We outsource zero processes.

To you, that means the product you are installing is the highest quality and longest lasting component on the market.

To us, that means you've selected a part we've spent years developing. Each Rock Hard 4x4 part has gone through more research and development and evolution than most people realize. While our parts may have the same striking look year after year, subtle revisions and refinements we implement maintain their status as the most durable and easy to install on the market.

We invite you to send us your feedback! Please email, call, write, or catch us on an off road trail near you to share your tales, share comments, and ask questions.

Phone: 844-762-5427 Fax: 308-754-5201 Email: <u>sales@rockhard4x4.com</u> Site: www.rockhard4x4.com Mail: ROCK HARD 4X4 PO BOX 186 Saint Paul, NE 68873

REMOVING FACTORY FRONT BUMPER (OPTIONAL AS YOU CAN ALSO SIMPLY LOOSEN FRONT BUMPER)

- 1. Remove upper valence by unscrewing two plastic body plugs. Sometimes it's easier to simply drill them out. Discard.
- Remove lower air dam by unclipping 4 plastic body plugs along front of bumper and 2 along back of air dam. Reinstall is optional.
- 3. Use a 18MM socket and 3" extension to remove 8 nuts on back of front bumper. 4 per frame horn on backside of bumper.
- 4. Unclip factory fog lights harness from passenger side frame rail (if equipped).
- 5. Slide factory front bumper off frame rails to expose remaining factory fog light wiring harness clips. Use wire cutters to cut zip ties, do not cut fog light wires.
- 6. Unclip factory fog lights from housings.
- 7. Remove front bumper from vehicle.

LOOSENING OF FACTORY FRONT BUMPER (FULL REMOVAL NOT NECESSARY)

- 1. Remove upper valence by unscrewing two plastic body plugs. Sometimes it's easier to simply drill them out. Discard.
- Remove lower air dam by unclipping 4 plastic body plugs along front of bumper and 2 along back of air dam. Reinstall is optional.
- 3. Use a 18MM socket and 3" extension to loosen 8 nuts on back of front bumper. 4 per frame horn on backside of bumper.

INSTALLING WINCH PLATE

PRO TIP: INSTALL AND REMOVE BOLTS INTO WINCH PLATE MOUNTING LEGS TO CLEAR OUT EXCESS POWDER COAT.

PRO TIPS: INSTALL WINCH PRIOR TO INSTALLING WINCH PLATE INTO FRAME. INSTALL HOOP (SOLD SEPARATELY) PRIOR TO INSTALLING WINCH PLATE.

- 1. Carefully side winch mount into frame brackets and align holes.
- Install two bolts with lock washers and flat washers using ³/₄" socket. Do not fully tighten at this time.
- 3. Reinstall bumper.
- 4. Align winch plate with tow hooks in bumper, tighten all hardware.

Rock Hard 4x4 Exclusive Limited Lifetime Warranty

Your Rock Hard 4x4® branded accessories are covered by the following Limited Warranty provided exclusively by Rock Hard 4x4., 1005 Twin Forks Lane, St. Paul, NE 68873.

This Limited Warranty is the only warranty made in connection with your purchase. Rock Hard 4x4 neither assumes nor authorizes any vendor, retailer or other person or entity to assume for it any other obligation or liability in connection with this product or Limited Warranty.

What is Covered: Subject to the terms, exclusions and limitations herein and with respect only to Rock Hard 4x4 branded accessories first sold in the United States, Rock Hard 4x4 warrants to the initial retail purchaser only that your Rock Hard 4x4 accessory shall be free of defects in material and workmanship for the lifetime of this product.

Rock Hard 4x4 reserves the rights to: (a.) require invoice or other proof your accessory is within the terms of this Limited Warranty as a condition of warranty service and, (b.) make future revisions to this product and Limited Warranty without prior notice or obligation to upgrade your product.

What is Not Covered: Your Rock Hard 4x4 Limited Warranty does not cover products or parts Rock Hard 4x4 determines to have been damaged by or subjected to: (a.) Installation damage, alteration, modification, combination with other parts, failure to maintain or improper repair or service, (b.) normal wear & tear, cosmetic damage or damage from moisture or water immersion, (c.) Acts of God, accidents, misuse, negligence, inadequate mounting or impact with vehicle(s), obstacles or other aspects of the environment, (d.) theft, vandalism or other intentional damage. (e.) powder coat, anodizing, or paint finish.

Remedy Limited to Repair/Replacement: The exclusive remedy provided hereunder shall, upon Rock Hard 4x4 inspection and at Rock Hard 4x4's option, be either repair or replacement of product or parts (new or refurbished) covered under this Limited Warranty. Customers requesting warranty consideration should first contact Rock Hard 4x4 to obtain a RGA number (308-750-4690). All labor, removal, shipping and installation costs are customer's responsibility.

Your Rights Under State Law: In consideration of the purchase price paid, neither Rock Hard 4x4 nor any independent Rock Hard 4x4 distributor/licensee are responsible for any time loss, rental costs, or for any incidental, consequential, punitive or other damages you may have or incur in connection with any part or product purchased.