

ROCK HARD 4X4 JEEP WRANGLER JK 2/4-DOOR 2011-2017 3.6L EVAP CANISTER RELOCATION KIT PART #: RH-6005-B **Installation Manual**



PACKING LIST:

- 1 CANISTER RELOCATION PLATE
- 1 NUT PLATE
- 1 EMERGENCY BRAKE DROP BRACKET
- 2 1/4" X 3/4" FLANGE BOLTS
- 2 ¼" NYLOCK NUTS
- 2 3/8" X 1" HEX BOLTS
- 2 3/8" STD FLAT WASHERS
- 2 19" X 5/8" RED HEATER HOSES
- 1 19" X 3/8" BLACK HEATER HOSE

Thank you for your purchase! Whether you bought this Rock Hard 4x4 product from one of our fantastic dealers or our factory direct team, we thank you for your business.

Rock Hard 4x4 is a family owned and operated business. We are headquartered in Saint Paul, Nebraska where we design, fabricate, and produce every single one of our products. Every single part we manufacture is 100% Made in the USA and exclusively in house by the Rock Hard 4x4 team.

We outsource zero processes.

To you, that means the product you are installing is the highest quality and longest lasting component on the market.

To us, that means you've selected a part we've spent years developing. Each Rock Hard 4x4 part has gone through more research and development and evolution than most people realize. While our parts may have the same striking look year after year, subtle revisions and refinements we implement maintain their status as the most durable and easy to install on the market.

We invite you to send us your feedback! Please email, call, write, or catch us on an off road trail near you to share your tales, share comments, and ask questions.

Phone: 844-762-5427
Fax: 308-754-5201
Email: sales@rockhard4x4.com
Site: www.rockhard4x4.com
Mail: ROCK HARD 4X4
PO BOX 186
Saint Paul, NE 68873

PLEASE NOTE: Some 2012+ models may require drilling a hole in rear cross member where tab installs. Some require removing the OEM cover that has wires going through it. This will expose a needed bolt hole.

- 1. Remove hoses and wire connector from canister, remove canister bracket from vehicle.
- 2. Bend bracket tab to remove canister from bracket.
- 3. Remove nuts from emergency cable wire bracket above rear axle housing.
- 4. Install Rock Hard 4x4 Emergency Brake Drop Bracket with factory nuts. *See photo 1.*



Photo 1

5. Install factory wire bracket on new drop bracket with two $\frac{1}{4}$ " x $\frac{3}{4}$ " flange bolt and two nylock nuts.

6. Cut hose with razor knife about 8" from end of hose (discard cut hose.)

See photo 2 and 3.





Photo 2 Photo 3

7. Install nut plate into frame on right (passenger) side above rear axle. A hammer tap may assist with install. Align with holes in frame. If a metal strap is in the way, unbolt strap, this will expose mounting hole. Some rare crossmembers do not have second hole. May require drilling.





Photo 4

8. Install canister in new bracket as shown in Photo 5. Bend table to hold into place.



Photo 5

9. Install canister on frame as shown in Photo 6 using two 3/8" x 1" bolts with flat washers.

PRO TIP: Lifting Jeep frame with jack may assist.



Photo 6

10. Reroute wiring and reconnect canister. Install hoses as shown in Photo 7.



Photo 7

CONGRATULATIONS! Now go wheel your rig with a whole new level of confidence and capability.

Please send photos of your install and wheeling adventures to pics@rockhard4x4.com. We love seeing our products on the trail!

Rock Hard 4x4 Exclusive Limited Lifetime Warranty

Your Rock Hard 4x4® branded accessories are covered by the following Limited Warranty provided exclusively by Rock Hard 4x4., 1005 Twin Forks Lane, St. Paul, NE 68873.

This Limited Warranty is the only warranty made in connection with your purchase. Rock Hard 4x4 neither assumes nor authorizes any vendor, retailer or other person or entity to assume for it any other obligation or liability in connection with this product or Limited Warranty.

What is Covered: Subject to the terms, exclusions and limitations herein and with respect only to Rock Hard 4x4 branded accessories first sold in the United States, Rock Hard 4x4 warrants to the initial retail purchaser only that your Rock Hard 4x4 accessory shall be free of defects in material and workmanship for the lifetime of this product.

Rock Hard 4x4 reserves the rights to: (a.) require invoice or other proof your accessory is within the terms of this Limited Warranty as a condition of warranty service and, (b.) make future revisions to this product and Limited Warranty without prior notice or obligation to upgrade your product.

What is Not Covered: Your Rock Hard 4x4 Limited Warranty does not cover products or parts Rock Hard 4x4 determines to have been damaged by or subjected to:
(a.) Installation damage, alteration, modification, combination with other parts, failure to maintain or improper repair or service, (b.) normal wear & tear, cosmetic damage or damage from moisture or water immersion, (c.) Acts of God, accidents, misuse, negligence, inadequate mounting or impact with vehicle(s), obstacles or other aspects of the environment, (d.) theft, vandalism or other intentional damage. (e.) powder coat, anodizing, or paint finish.

Remedy Limited to Repair/Replacement: The exclusive remedy provided hereunder shall, upon Rock Hard 4x4 inspection and at Rock Hard 4x4's option, be either repair or replacement of product or parts (new or refurbished) covered under this Limited Warranty. Customers requesting warranty consideration should first contact Rock Hard 4x4 to obtain a RGA number (308-750-4690). All labor, removal, shipping and installation costs are customer's responsibility.

Your Rights Under State Law: In consideration of the purchase price paid, neither Rock Hard 4x4 nor any independent Rock Hard 4x4 distributor/licensee are responsible for any time loss, rental costs, or for any incidental, consequential, punitive or other damages you may have or incur in connection with any part or product purchased.