

ROCK HARD 4X4 JEEP WRANGLER JK 2/4-DOOR 2007-2017 ROCKER GUARD PART #: RH-6006-T/S / RH-6007-T/S Installation Manual



INSTALLATION VIDEO AVAILABLE YOU TUDE

PLEASE VISIT YOUTUBE.COM/C/ROCKHARD4X4

Customer Service / Tech Support: <u>sales@rockhard4x4.com</u> Thank you for your purchase! Please read all instructions carefully prior to beginning installation of your Rock Hard 4x4 product.

PACKING LIST:

- **1 LEFT ROCKER GUARD**
- 1 RIGHT ROCKER GUARD
- 24 ¼" X 20 X ¾" WHIZ BOLTS
- 24 ¼" MOLLY JACKS
- **1 MOLLY NUT INSERT TOOL**
- 6- 12MM X 1.75 X 150MM BOLTS
- 4 2" SPACERS
- 2 111/16" spacers
- 24 SMALL ROUND PLASTIC ROUND PLUGS
- 5 SMALL RECTANGULAR PLASTIC END CAP PLUGS
- 1 STEP BIT

REQUIRED TOOLS:

RUBBER MALLET OR HAMMER ³⁄₄" SOCKET FLOOR JACK OR BOTTLE JACK SHARPIE BLUE PAINTERS TAPE (OPTIONAL) DRILL FOR INCLUDED STEP BIT

Thank you for your purchase! Whether you bought this Rock Hard 4x4 product from one of our fantastic dealers or our factory direct team, we thank you for your business.

Rock Hard 4x4 is a family owned and operated business. We are headquartered in Saint Paul, Nebraska where we design, fabricate, and produce every single one of our products. Every single part we manufacture is 100% Made in the USA and exclusively in house by the Rock Hard 4x4 team.

We outsource zero processes.

To you, that means the product you are installing is the highest quality and longest lasting component on the market.

To us, that means you've selected a part we've spent years developing. Each Rock Hard 4x4 part has gone through more research and development and evolution than most people realize. While our parts may have the same striking look year after year, subtle revisions and refinements we implement maintain their status as the most durable and easy to install on the market.

We invite you to send us your feedback! Please email, call, write, or catch us on an off road trail near you to share your tales, share comments, and ask questions.

Phone: 844-762-5427 Fax: 308-754-5201 Email: <u>sales@rockhard4x4.com</u> Site: www.rockhard4x4.com Mail: ROCK HARD 4X4 PO BOX 186 Saint Paul, NE 68873

- 1. Remove factory installed rocker guards (if applicable) from vehicle.
- Clean vehicle body surface at installation site to prevent accidental scratching and paint scuffing. This is a great opportunity to mask the area with paint safe "painters tape" – just remember to remove tape prior to final install of rocker guard.
- 3. Remove the 2 (if 2-door) or 3 (if 4-door) factory body bolts (bottom of frame rails).
- 4. You may want assistance for this part: Slide rocker guard into place by lining up bottom of boat side near frame and top section against vehicle body.
- Install supplied 2" spacers between rocker guard and body. SHORTER 11/16" spacers towards front of vehicle. 2-door JK uses 4 2" spacers, no shorter spacers included.
- 6. Tighten the lower bolts while lifting on the outside of the rocker. This will lift the rocker guard up evenly.
- 7. Once rocker guard is secured and the bolt-holes are lined up against vehicle body evenly and tightly, ensure door opens and closes without obstruction. Assume this is final fitment so make any adjustments you'd like for a tight fitting rocker guard.
- 8. Using a sharpie or other marking device, mark holes where you will drill along tub rail.
- 9. Remove rocker guard from body and set aside. This is where the fun starts.

Customer Service / Tech Support: <u>sales@rockhard4x4.com</u> Thank you for your purchase! Please read all instructions carefully prior to beginning installation of your Rock Hard 4x4 product.

- 10. Using supplied step bit and a steady hand, begin drilling holes into vehicle body. Do not drill holes larger than nut insert. It may take a moment for step bit to "bite" sheet metal but once you penetrate the step bit will begin cutting easily. Take your time and you'll do a great job.
- 11. Install nut inserts into vehicle body using provided tool.
- 12. Reinstall spacers and rocker guard into body mounts. Tighten the lower bolts while lifting on the outside of the rocker guard. This will lift the rocker guard up evenly. Only snug lower bolts at this time.
- 13. Visually inspect that nut inserts line up with rocker guard bolt holes. Install $\frac{1}{4}$ " x 20 x $\frac{3}{4}$ " bolts.
- 14. Tighten lower body mount bolts.
- 15. Install supplied plastic plugs into each rocker guard bolt hole. These prevent water and debris from entering rocker guard and gives you a clean, heavy duty look.
- 16. Repeat process for other side of vehicle.
- 17. Locate and install supplied rectangular plastic end caps into Rock Hard 4x4 rocker guards. They may require some "love" to secure the plugs in place. A light hammer tap or good bump with your palm should be enough. The tight fit ensures they do not fall out after years of use and abuse.

Rock Hard 4x4 Exclusive Limited Lifetime Warranty

Your Rock Hard 4x4® branded accessories are covered by the following Limited Warranty provided exclusively by Rock Hard 4x4., 1005 Twin Forks Lane, St. Paul, NE 68873.

This Limited Warranty is the only warranty made in connection with your purchase. Rock Hard 4x4 neither assumes nor authorizes any vendor, retailer or other person or entity to assume for it any other obligation or liability in connection with this product or Limited Warranty.

What is Covered: Subject to the terms, exclusions and limitations herein and with respect only to Rock Hard 4x4 branded accessories first sold in the United States, Rock Hard 4x4 warrants to the initial retail purchaser only that your Rock Hard 4x4 accessory shall be free of defects in material and workmanship for the lifetime of this product.

Rock Hard 4x4 reserves the rights to: (a.) require invoice or other proof your accessory is within the terms of this Limited Warranty as a condition of warranty service and, (b.) make future revisions to this product and Limited Warranty without prior notice or obligation to upgrade your product.

What is Not Covered: Your Rock Hard 4x4 Limited Warranty does not cover products or parts Rock Hard 4x4 determines to have been damaged by or subjected to: (a.) Installation damage, alteration, modification, combination with other parts, failure to maintain or improper repair or service, (b.) normal wear & tear, cosmetic damage or damage from moisture or water immersion, (c.) Acts of God, accidents, misuse, negligence, inadequate mounting or impact with vehicle(s), obstacles or other aspects of the environment, (d.) theft, vandalism or other intentional damage. (e.) powder coat, anodizing, or paint finish.

Remedy Limited to Repair/Replacement: The exclusive remedy provided hereunder shall, upon Rock Hard 4x4 inspection and at Rock Hard 4x4's option, be either repair or replacement of product or parts (new or refurbished) covered under this Limited Warranty. Customers requesting warranty consideration should first contact Rock Hard 4x4 to obtain a RGA number (308-750-4690). All labor, removal, shipping and installation costs are customer's responsibility.

Your Rights Under State Law: In consideration of the purchase price paid, neither Rock Hard 4x4 nor any independent Rock Hard 4x4 distributor/licensee are responsible for any time loss, rental costs, or for any incidental, consequential, punitive or other damages you may have or incur in connection with any part or product purchased.

Customer Service / Tech Support: <u>sales@rockhard4x4.com</u> Thank you for your purchase! Please read all instructions carefully prior to beginning installation of your Rock Hard 4x4 product.