

ROCK HARD 4X4 JEEP WRANGLER JL AND GLADIATOR JT 2018 - CURRENT FRONT BUMPER (ALL) **PART #: 902XX Installation Manual**



PACKING LIST:

- 1 FRONT BUMPER
- 8 ½" X 3" BUTTON HEAD BOLTS
- 8 1" X 1 3/8" SPACERS
- 8 ½" WASHERS
- 8 NYLOCK NUTS
- 8 10 X 3/4" SELF DRILLING SCREWS
- 1 1/2" THIN NUT BOLT FOR ZEON INSTALL
- 1 ½" X 2-3/4" BUTTON HEAD BOLT FOR ZEON INSTALL
- 2 2" X 2" PLASTIC PLUGS
- 1 JL HALOGEN LED FOG KIT (IF APPLICABLE) COMPRISED OF 10M AND 2X Z-SHAPED MOUNTS

ALUMINUM FRONT BUMPER ONLY:

2 - LONG RECTANGULAR PLATES (HOLES EACH END)

REQUIRED TOOLS:

WIRE OR ZIP TIE SNIPS
3/4" SOCKET AND WRENCH
3" SOCKET WRENCH EXTENSION
13MM SOCKET
16MM SOCKET
5/16" OR 8MM ALLEN WRENCH
5/16" OR 8MM SOCKET

Thank you for your purchase! Whether you bought this Rock Hard 4x4 product from one of our fantastic dealers or our factory direct team, we thank you for your business.

Rock Hard 4x4 is a family owned and operated business. We are headquartered in Saint Paul, Nebraska where we design, fabricate, and produce every single one of our products. Every single part we manufacture is 100% Made in the USA and exclusively in house by the Rock Hard 4x4 team.

We outsource zero processes.

To you, that means the product you are installing is the highest quality and longest lasting component on the market.

To us, that means you've selected a part we've spent years developing. Each Rock Hard 4x4 part has gone through more research and development and evolution than most people realize. While our parts may have the same striking look year after year, subtle revisions and refinements we implement maintain their status as the most durable and easy to install on the market.

We invite you to send us your feedback! Please email, call, write, or catch us on an off road trail near you to share your tales, share comments, and ask questions.

Phone: 844-762-5427
Fax: 308-754-5201
Email: sales@rockhard4x4.com
Site: www.rockhard4x4.com
Mail: ROCK HARD 4X4
PO BOX 186

Saint Paul, NE 68873

REMOVING FACTORY FRONT BUMPER

- Remove upper valence by unscrewing two plastic body plugs. Sometimes it's easier to simply drill them out.
 Discard – will not be reused. There may be 6 additional if plastic bumper.
- 2. Unplug front bumper harness, located along passenger side frame rail.
- 3. If equipped: use 13MM socket to remove front bumper lower skid plate bolts.
- 4. Use a 18MM socket and 3" extension to remove 8 nuts on back of front bumper. 4 per frame cap.
- 5. If equipped: use 16MM socket to remove skid plate mounting bracket (stamped plate between crash bar mounts).
- 6. Unclip/Unbolt factory fog lights from housings.
- 7. If reusing factory fog lights, use Phillips screwdriver to unscrew 4 screws per light housing (if equipped).
- 8. Remove front bumper from vehicle. If reusing OEM fog lights, remove fog light harness from front bumper housing.

INSTALLING ROCK HARD 4X4 FRONT BUMPER

1. Install OEM fog lights into front bumper (if applicable) using included 10M self-tapping screws. If LED, no modification needed, swap driver and passenger side fogs to install.

HALOGEN FOG STEPS:

• Use 1x Z-shaped adapter and 2x 10M self-tapping screw per fog light.

• Install z-shaped adapter with tab oriented as shown below using 1x adapter per mount. Tab faces center of Jeep. You will use 2x center holes in bumper trim ring.



 Trim upper ear off plastic mount. Passenger side fog shown as example. Install fog light.



2. Slide new Rock Hard 4x4 front bumper onto frame. Leave approximately 2" between end of frame caps and inside of front bumper.

- 3. Use eight 1" x 1 3/8" long spacers between front end of frame and new bumper.
 - PRO TIP: All winches, except for some imports, will use 8x long spacers between Jeep frame and nut. Some import winches have wires that come directly out of back of winch and would normally hit grille. In this case, use short spacers plus long spacers to provide enough room to run wire between grille and bumper this may however cause winch to hit frame horns.
- 4. Install eight ½" x 3" button head bolts from front of bumper through spacers and into frame, washers and nuts. Use a ¾" socket on back of nut, 5/16" or 8MM allen for bolt head.

PRO TIP: If installing Rock Hard 4x4 tow bar brackets, install at this time with supplied hardware in tow bar bracket kit. Tow bar bracket kits sold separately. Learn more at www.rockhard4x4.com/towing

PRO TIP: If installing a Warn ZEON winch, use one $\frac{1}{2}$ " x 2 $\frac{3}{4}$ " button head and one $\frac{1}{2}$ " thin nylock nut on top inner driver side frame mount for winch clearance.

- 5. Install eight ½" washers and eight nylock nuts on backside of frame horns.
- 6. Reroute wiring harness to fog lights and reconnect fog lights to harness.

WINCH INSTALL TIPS:

- A. Install winch using supplied bolts and hardware.
- B. If installing a winch into a Rock Hard 4x4 aluminum front bumper, use supplied two long rectangular washers for bottom side of winch plate for added strength.

Rock Hard 4x4 Exclusive Limited Lifetime Warranty

Your Rock Hard 4x4® branded accessories are covered by the following Limited Warranty provided exclusively by Rock Hard 4x4., 1005 Twin Forks Lane, St. Paul, NE 68873.

This Limited Warranty is the only warranty made in connection with your purchase. Rock Hard 4x4 neither assumes nor authorizes any vendor, retailer or other person or entity to assume for it any other obligation or liability in connection with this product or Limited Warranty.

What is Covered: Subject to the terms, exclusions and limitations herein and with respect only to Rock Hard 4x4 branded accessories first sold in the United States, Rock Hard 4x4 warrants to the initial retail purchaser only that your Rock Hard 4x4 accessory shall be free of defects in material and workmanship for the lifetime of this product.

Rock Hard 4x4 reserves the rights to: (a.) require invoice or other proof your accessory is within the terms of this Limited Warranty as a condition of warranty service and, (b.) make future revisions to this product and Limited Warranty without prior notice or obligation to upgrade your product.

What is Not Covered: Your Rock Hard 4x4 Limited Warranty does not cover products or parts Rock Hard 4x4 determines to have been damaged by or subjected to:
(a.) Installation damage, alteration, modification, combination with other parts, failure to maintain or improper repair or service, (b.) normal wear & tear, cosmetic damage or damage from moisture or water immersion, (c.) Acts of God, accidents, misuse, negligence, inadequate mounting or impact with vehicle(s), obstacles or other aspects of the environment, (d.) theft, vandalism or other intentional damage. (e.) powder coat, anodizing, or paint finish.

Remedy Limited to Repair/Replacement: The exclusive remedy provided hereunder shall, upon Rock Hard 4x4 inspection and at Rock Hard 4x4's option, be either repair or replacement of product or parts (new or refurbished) covered under this Limited Warranty. Customers requesting warranty consideration should first contact Rock Hard 4x4 to obtain a RGA number (308-750-4690). All labor, removal, shipping and installation costs are customer's responsibility.

Your Rights Under State Law: In consideration of the purchase price paid, neither Rock Hard 4x4 nor any independent Rock Hard 4x4 distributor/licensee are responsible for any time loss, rental costs, or for any incidental, consequential, punitive or other damages you may have or incur in connection with any part or product purchased.