



**rockGEAR™** — RS62115

Rancho HD Front Adjustable Track Bar

Fits 2016 – 2007 Jeep Wrangler JK

READ ALL INSTRUCTIONS THOROUGHLY FROM START TO FINISH BEFORE BEGINNING INSTALLATION

## Parts List

P/N	DESCRIPTION	QTY.
RS881029B	HD Front Adjustable Track Bar- JK	1
RS82115	Instructions	1



1) ☐ Park vehicle on a level surface. Set the parking brake and chock wheels.

2) ☐ Measure the axle center by measuring the distance from the outside face of the tire to fender edge. Use a plumb-bob or straight edge for reference. Record the measurements below:

Driver Side \_\_\_\_\_ Passenger Side \_\_\_\_\_

3) ☐ Remove the track bar to frame bracket nut and bolt.

4) ☐ Remove the track bar to axle bracket flag nut and bolt. Do not use impact wrench if flag nut is installed.

NOTE: Remove steering stabilizer if it is preventing removal of track bar bolt.

5) ☐ Remove track bar.

6) ☐ Adjust length of new Ranch track bar RS881029B using old track bar and measurements from step 2 as guide.

If axle is shifted to the passenger side of vehicle adjust RS881029B shorter than old track bar.

If axle is shifted to the driver side of vehicle adjust RS881029B longer than old track bar.

Adjust bar half the amount that axle is shifted.

**CAUTION:** Do not adjust longer than 33.4" with no more than 1.4" exposed threads on rod end.

7) ☐ Attach non-adjustable end of track bar RS881029B to frame bracket using OE hardware.

8) ☐ Attach adjustable end of track bar RS881029B to axle bracket using OE hardware.

If holes do not line up, have an assistant SLOWLY turn the steering wheel to align holes.

9) ☐ Torque upper and lower mounting hardware to 125 lb-ft.

10) ☐ Torque jam nut to 150 lb-ft.

**IMPORTANT:** re-torque mounting hardware and jam nut after first 100 miles, and every time vehicle is driven off-road.



Rancho Technical Department 1-734-384-7804.