

TACTIK® Front Inner Fender Liner

Installation Manual:
for '07-'18 Wrangler JK



⚠ WARNING ⚠

TO REDUCE RISK OF SERIOUS INJURY OR PROPERTY DAMAGE: READ ALL SAFETY MESSAGES AND UNDERSTAND ALL INSTRUCTIONS AND PROCEDURE NOTICES BEFORE ATTEMPTING TO INSTALL OR USE THIS PRODUCT.

⚠ WARNING ⚠

RISK OF EYE INJURY! SAFETY GLASSES MUST BE WORN AT ALL TIMES WHILE INSTALLING OR MAINTAINING THIS PRODUCT. TORQUE AND RECHECK FASTENERS AFTER 250 MILES AND FREQUENTLY THEREAFTER. DO NOT USE IF DAMAGED.

NOTICE

SLIGHT MODIFICATION INCLUDING CUTTING AND DRILLING IS REQUIRED TO COMPLETE THIS INSTALLATION.

A FEW WORDS ABOUT PRODUCT SAFETY:

Your Tactik Inner Fender Liner is intended to enhance the appearance and enjoyment of your off road capable vehicle. Follow safety information and installation recommendations. Throughout these instructions is important safety information that is generally preceded by one of three signal words indicating the relative risk of injury, property damage or adverse consequence.

The signal words mean:

⚠ WARNING ⚠

A HAZARDOUS SITUATION WHICH, IF NOT AVOIDED, COULD RESULT IN DEATH OR SERIOUS INJURY. YOU CAN BE KILLED OR SERIOUSLY HURT IF YOU DON'T FOLLOW INSTRUCTIONS.

⚠ CAUTION ⚠

A HAZARDOUS SITUATION WHICH, IF NOT AVOIDED, COULD RESULT IN A MINOR OR MODERATE INJURY. YOU CAN BE MODERATELY HURT AND ALSO MAY SUFFER PROPERTY DAMAGE IF YOU DON'T FOLLOW INSTRUCTIONS.

NOTICE

CAREFUL ATTENTION IS REQUIRED TO THIS INSTRUCTION OR OPERATION BUT DOES GENERALLY NOT RELATE TO PERSONAL INJURY. DAMAGE TO YOUR QUADRATEC® PRODUCT OR OTHER PROPERTY MAY RESULT IF YOU DON'T FOLLOW INSTRUCTIONS.

BEFORE YOU BEGIN INSTALLATION:

Congratulations on your purchase of Tactik Inner Fender Liners for your Jeep® Wrangler. This custom fit liner has been designed for use with the factory fender flare to give a great custom look and protect the inner wheel well. When unpacking, check to make sure all parts are included and not damaged due to shipping. If any part is missing or broken, please call Customer Service at 800-745-6037 as soon as possible. Thank you again for your purchase and let's start the installation process.

⚠ CAUTION ⚠

READ ALL SAFETY MESSAGES AND ALWAYS WEAR SAFETY GLASSES WHEN WORKING WITH TOOLS.

⚠ WARNING ⚠

ALWAYS USE EXTREME CAUTION WHEN DRILLING OR CUTTING ON A VEHICLE OR PARTS. THOROUGHLY INSPECT THE AREA TO BE DRILLED OR CUT, ON BOTH SIDES OF MATERIAL, PRIOR TO MODIFICATION AND RELOCATE ANY OBJECTS THAT COULD BECOME DAMAGED.

NOTICE

WE ALSO RECOMMEND THAT YOU HAVE A HELPER NEARBY AS SOME OF THE STEPS OUTLINED BELOW WILL BE MUCH EASIER WITH THE HELP OF ANOTHER SET OF HANDS.


NOTICE

CHECK THE SURROUNDING AREA BEFORE DRILLING TO AVOID ACCIDENTAL DAMAGE TO EXISTING COMPONENTS OR WIRING.



KIT CONTENT LIST:


- A. Inner Fender Liner (x2)
- B. M6 Flat Washer/Spacer (x6)
- C. M6 Nylock Nut (x6)
- D. M6-1.0 x 15mm Button Head Bolt (x6)
- E. Self-tapping Screw (x4)
- F. 4mm Hex Wrench



REQUIRED TOOLS:

- Safety Glasses
- 8mm Socket
- 10mm Socket / Wrench
- Ratchet
- Pry Tool
- 7/64" Drill Bit
- Drill

STEP 1



Remove the 6 bolts (circled) holding the fender flares and liners (Fig 1) using a 10mm socket and ratchet. (Fig 2) Retain for reassembly.

STEP 2



Locate the wiring harness for the running lights and side markers. Release the clip and pull apart. (Fig 3)

STEP 3




Using even force and hands grasping the edge of the fender flares, pull directly away from the quarter panel. (Fig 4) There will be tension on from the clips and you will find resistance until they release. Some clips may stay attached to the quarter panel. (Fig 5) Remove with a pry tool and reattach to the fender flare.

STEP 4




Locate the four retainer clips shown with circles. (Fig 6) Using a pry tool, remove each one. (Fig 7)

STEP 5



Disconnect the inner fender liner from the fender flare by using a pry tool between each piece at the plastic retaining rivets and pry out. (Fig 8) Once each rivet has been released, slide the inner fender liner away from the flare. (Fig 9)

STEP 6




Note that the retaining rivets from the previous step remain. (Fig 10) These can be cut away as they will not be reused. (Fig 11)

STEP 7




In order to perform Step 7, you will need to draw a line on the inside of the fender, and then cut along the line you drew. IT'S VERY IMPORTANT TO DRAW THE LINE BEFORE YOU BEGIN TO CUT! Using a marker or a paint pen, draw the line as shown in FIG 12. Next, using a cutting tool, carefully cut along the line that you drew. This line may need to be adjusted slightly after cutting. (Fig 13). **Remember:** You can always remove more material, but you can't add it back on.

STEP 8




Remove the wiring group from the sheet metal by releasing the retaining clip. This will allow the wiring to move freely and be a little longer to reach the wiring harness a little later. (Fig 14) Using a 7/64" drill bit, drill a pilot hole to be used with a self-tapping screw in Step 8. (Fig 15)

STEP 9



Holding the inner liner and fender flare together, slide the assembly back onto the quarter panel allowing the clips to engage and hold the flare in place. Start with the bolt toward the center. (Fig 16) From underneath begin to replace the factory 10mm bolts to hold in place. (Fig 17)

STEP 10



Insert and tighten the bolt on the structural brace to secure the fender and liner to the vehicle. (Fig 18) Insert and tighten the self-taping screw into the pilot hole drilled previously. (Fig 19)

STEP 11



Using the 7/64" drill bit and using the liner as a guide, drill a pilot hole for the remaining self-tapping screw. Insert and tighten the self-tapping screw. (Fig 20) Tighten remaining 10mm bolts to secure the fender liner and flare. (Fig 21)

Complete



Pull the wiring harness around to the front of the flare so that the connectors can be reconnected and routed cleanly. Use a zip tie, if necessary, to secure harness up and out of the way. Repeat from Step 1 on the other side of the vehicle.

TACTIK® Exclusive One Year Limited Warranty

Your TACTIK® branded accessories are covered by the following Limited Warranty provided exclusively by TACTIK® located at 1028 Saunders Lane, West Chester PA 19380.

This **Limited Warranty** is the only warranty made in connection with your purchase. TACTIK® neither assumes nor authorizes any vendor, retailer or other person or entity to assume for it any other obligation or liability in connection with this product or **Limited Warranty**.

What is Covered: Subject to the terms, exclusions and limitations herein and with respect only to TACTIK® branded accessories first sold in the United States, TACTIK® warrants to the initial retail purchaser only that your TACTIK® accessory shall be free of defects in material and workmanship: **for a period of one (1) year from date of retail purchase.**

This **Limited Warranty** is not assignable and shall terminate upon sale of the vehicle upon which the TACTIK® accessory is installed or other transfer to third persons.

All other warranties are hereby disclaimed, except to the extent prohibited by applicable law in which case any implied warranty of merchantability or fitness for a particular purpose on this product is limited to 1 year from date of initial retail sale. TACTIK® reserves the rights to: (a.) require invoice or other proof your accessory is within the terms of this **Limited Warranty** as a condition of warranty service and, (b.) make future revisions to this product and **Limited Warranty** without prior notice or obligation to upgrade your product.

What is Not Covered:

Your TACTIK® **Limited Warranty** does not cover products or parts TACTIK® determines to have been damaged by or subjected to: (a.) installation damage, alteration, modification, combination with other parts, failure to maintain or improper repair or service, (b.) normal wear & tear, cosmetic damage or damage from moisture or water immersion, (c.) Acts of God, accidents, misuse, negligence, inadequate mounting or impact with vehicle(s), obstacles or other aspects of the environment, (d.) theft, vandalism or other intentional damage.

Remedy Limited to Repair/Replacement: The exclusive remedy provided hereunder shall, upon TACTIK® inspection and at TACTIK's option, be either repair or replacement of product or parts (new or refurbished) covered under this Limited Warranty. Customers requesting warranty consideration should first contact TACTIK® to obtain a RGA number via telephone at 800-603-4064, or initiate customer service by email at: customerservice@tactik4x4.com. All labor, removal, shipping and installation costs are customer's responsibility.

Other Limitations - Exclusion of Damages - Your Rights Under State Law:

In consideration of the purchase price paid, neither TACTIK® nor any independent TACTIK® distributor/licensee are responsible for any time loss, rental costs, or for any incidental, consequential, punitive or other damages you may have or incur in connection with any part or product purchased. Your exclusive remedy hereunder for covered parts is repair/replacement as described above.

This **Limited Warranty** gives you specific rights. You may also have other rights that vary from state to state. For example, some states do not allow limitations of how long an implied warranty lasts and /or do not allow the exclusion or limitation of incidental or consequential damages, so the limitations and exclusions herein may not apply to you.

©TACTIK® 2022 All Rights Reserved. A4 Version
Instructions Part #12999.3261

TACTIK®