

# TACTIK® Replacement Grille

## Installation & Use Instructions:

For '18 - Current (JL & JT) Wranglers #13131-10XX

### ! WARNING !

TO REDUCE RISK OF SERIOUS INJURY OR PROPERTY DAMAGE: READ ALL SAFETY MESSAGES AND UNDERSTAND ALL INSTRUCTIONS AND PROCEDURE NOTICES BEFORE ATTEMPTING TO INSTALL OR USE THIS PRODUCT.

### ! CAUTION !

RISK OF EYE INJURY! SAFETY GLASSES MUST BE WORN AT ALL TIMES WHILE INSTALLING OR MAINTAINING THIS PRODUCT. DO NOT USE IF DAMAGED.

### ! CAUTION !

IF EQUIPPED WITH LIGHTING, WHEN ROUTING ELECTRICAL WIRES, ALWAYS AVOID PINCHING WIRES. ALWAYS AVOID HOT OR MOVING COMPONENTS. ALWAYS SECURE WIRES WITH WIRE TIES.



## PARTS LIST

Grille - QTY 1  
Grille Bracket - QTY 2  
Phillips Head Bracket Screws - QTY 4  
Plastic Retaining Push Pins - QTY 6  
Rubber Hood/Grille Guard - QTY 1  
Retaining Clips - QTY 8  
M4 Bolts - QTY 8  
M4 Nuts - QTY 8  
Lighting Wire - QTY 1 (LED Light option only)

## REQUIRED TOOLS

Safety Glasses  
Forked Clip/Removal Tool  
Phillips Screwdriver  
Ratchet  
10MM Socket  
8MM Socket

## GRILLE PREPARATION WITH LIGHTING OPTION -STEP 1

FIG 1








FIG 2



Put on safety glasses. Using the Fork Removal tool, carefully remove the weather stripping from the top of the factory grille. Next, detach both the right and left grille pads from the top of the factory grille by removing the two push pins on each side. Place the provided grille guard onto the top of the new grille. Reinstall the right and left grille pads using the factory push pins. Using a Phillips head screwdriver and an 8mm socket, secure the grille guard by installing the eight M4 bolts and eight M4 nuts into the designated holes. Install the weather stripping on the top of the new grille (FIG 1 & 2).




## GRILLE PREPARATION WITH LIGHTING OPTION - STEP 2





Begin by installing the factory weather stripping onto the new grille, starting from either the right or left side. Next, connect all five light connectors to the grille. If you purchase a grille without LED lighting, proceed to installation Step 1. Finally, secure the grille by attaching the eight provided retainer clips (FIG 3 & 4).

## INSTALLATION - STEP 1



Use the removal tool to take out the six factory plastic push pins at the specified locations and detach the factory grille (FIG 5). Remove the factory grille and either store or dispose of it (FIG 6).


## STEP 2



Find the eight cutouts on the inner grille frame mount in the specified locations (FIG 7 & 8).



## STEP 3




If you are installing a grille with lighting options, make sure to disconnect the battery ground terminal first. Find the driver's side fender and locate the two 10mm bolts securing the fender liner. Use a 10mm socket to remove the bolts (FIG 9). Use a pry tool to remove the two plastic push pins. Pull back the fender liner. Then, locate the wire connector for the side marker (FIG 10).

## STEP 4



Disconnect the wire connector for the side marker. Position the new grille at the front of the Jeep, ensuring the grille lighting wire is routed through the lower corner of the headlight (FIG 11). On the male side of the side marker wiring, install two wire couplers—one on the white/brown wire and one on the black wire (FIG 12).

## STEP 5




Connect the red wire from the grille lighting to the white/brown wire, and connect the black wire from the grille lighting to the black wire (FIG 13). Reconnect the side marker wire. Neatly bundle the excess wiring inside the fender and secure it using electrical tape and a wire tie (Not Included) (FIG 14).



## STEP 6

FIG 15



Next, reinstall the fender liner by reversing the steps in Step 3 of Grille Installation with lighting option (FIG 15). Return to Installation Step 1 and securely install the new grille onto your Jeep.

## STEP 7

Gently press the grille into place, ensuring each retaining bracket locks into the specified locations on the grille frame (FIG 16).

FIG 16




## STEP 8

FIG 17




FIG 18



Insert the six plastic push pins to secure the new grille in the specified locations (FIG 17 & 18).

## STEP 9

FIG 19



Recheck the rubber hood/grille guard over the center of the grille's top edge and the bottom of the hood. (Fig 19).

## INSTALLATION COMPLETE



Installation is now complete. Enjoy your new Tactik grille replacement.

# **TACTIK®** Exclusive One Year Limited Warranty

Your TACTIK® branded accessories are covered by the following Limited Warranty provided exclusively by TACTIK® located at 1028 Saunders Lane, West Chester PA 19380.

This **Limited Warranty** is the only warranty made in connection with your purchase. TACTIK® neither assumes nor authorizes any vendor, retailer or other person or entity to assume for it any other obligation or liability in connection with this product or **Limited Warranty**.

**What is Covered:** Subject to the terms, exclusions and limitations herein and with respect only to TACTIK® branded accessories first sold in the United States, TACTIK® warrants to the initial retail purchaser only that your TACTIK® accessory shall be free of defects in material and workmanship: **for a period of one (1) year from date of retail purchase.**

This **Limited Warranty** is not assignable and shall terminate upon sale of the vehicle upon which the TACTIK® accessory is installed or other transfer third persons.

All other warranties are hereby disclaimed, except to the extent prohibited by applicable law in which case any implied warranty of merchantability or fitness for a particular purpose on this product is limited to 1 year from date of initial retail sale. TACTIK® reserves the rights to: (a.) require invoice or other proof your accessory is within the terms of this **Limited Warranty** as a condition of warranty service and, (b.) make future revisions to this product and **Limited Warranty** without prior notice or obligation to upgrade your product.

#### **What is Not Covered:**

Your TACTIK® **Limited Warranty** does not cover products or parts TACTIK® determines to have been damaged by or subjected to: (a.) installation damage, alteration, modification, combination with other parts, failure to maintain or improper repair or service, (b.) normal wear & tear, cosmetic damage or damage from moisture or water immersion, (c.) Acts of God, accidents, misuse, negligence, inadequate mounting or impact with vehicle(s), obstacles or other aspects of the environment, (d.) theft, vandalism or other intentional damage.

**Remedy Limited to Repair/Replacement:** The exclusive remedy provided hereunder shall, upon TACTIK® inspection and at TACTIK's option, be either repair or replacement of product or parts (new or refurbished) covered under this **Limited**

**Warranty.** Customers requesting warranty consideration should first contact TACTIK® to obtain a RGA number via telephone at 800-603-4064, or initiate customer service by email at: [customerservice@tactik4x4.com](mailto:customerservice@tactik4x4.com). All labor, removal, shipping and installation costs are customer's responsibility.

#### **Other Limitations - Exclusion of Damages - Your Rights Under State Law:**

In consideration of the purchase price paid, neither TACTIK® nor any independent TACTIK® distributor/licensee are responsible for any time loss, rental costs, or for any incidental, consequential, punitive or other damages you may have or incur in connection with any part or product purchased. Your exclusive remedy hereunder for covered parts is repair/replacement as described above.

This **Limited Warranty** gives you specific rights. You may also have other rights that vary from state to state. For example, some states do not allow limitations of how long an implied warranty lasts and /or do not allow the exclusion or limitation of incidental or consequential damages, so the limitations and exclusions herein may not apply to you.

©TACTIK® 2025 All Rights Reserved. A4 Version

**Instructions Part #12999.5167**

**TACTIK®**