2650-1654-77 Rev. A



### QUESTIONS?

If after completely reading these instructions you have questions regarding the operation or installation of your instrument(s), please contact AutoMeter Technical Service at 866-248-6357. You may also email us at service@autometer.com.

Additional information can also be found at http://www.autometer.com

## Installation 1. Check that you have all parts required for installation. 2. Disconnect the negative (-) battery cable. 3. Gauge mounts in either $2\frac{1}{16}$ " or $3\frac{3}{8}$ " hole depending on gauge size purchased. Use supplied bracket to secure to dash. 4. Reconnect negative (-) battery cable. CAN LO --Green CAN HI White **CAUTION!** As a safety precaution, the red wire of this product should be fused before connecting to the 12V ignition switch. We recommend using a 3 AMP automotive type fuse. **BLACK FUSE** (SEE CAUTION) BATTERY + 12V/24V CONNECTION GOOD ENGINE GROUND DO NOT CONNECT TO ALTERNATOR

Mating Connector: DT06-6S

# Configuration

Gauge comes configured with white lighting and no warnings. If warnings are wanted/needed or you want to change the lighting color you will need to purchase a PEAK System USB to CAN Adapter (MFG P/N: IPEH-002021) and programming cable (AutoMeter P/N: 880687). Go to www.autometer.com and search for your iCAN model to download the iCAN Configuration Programming tool and instructions.

CAN Low

## **SERVICE**

For service send your product to AutoMeter in a well packed shipping carton. Please include a note explaining what the problem is along with your phone number. If you are sending product back for Warranty adjustment, you must include a copy (or original) of your sales receipt from the place of purchase.

### 12 MONTH LIMITED WARRANTY

AutoMeter Products, Inc. warrants to the consumer that all AutoMeter High Performance products purchased from an Authorized AutoMeter Reseller will be free from defects in material and workmanship for a period of twelve (12) months from date of the original purchase. Products that fail within this 12 month warranty period will be repaired or replaced at AutoMeter's option, when determined by AutoMeter that the product failed due to defects in material or workmanship. This warranty is limited to the repair or replacement of parts in the AutoMeter High Performance product and the necessary labor done by AutoMeter to effect the repair or replacement of the AutoMeter High Performance Product. In no event shall AutoMeter's cost to repair or replace an AutoMeter High Performance Product. Nor shall AutoMeter Products, Inc. be responsible for special, incidental or consequential damages or costs incurred due to the failure of an AutoMeter High Performance Product. This warranty applies only to the original purchaser of the AutoMeter High Performance Products purchased from an Authorized AutoMeter Reseller. All implied warranties shall be limited in duration to the said 12 month warranty period. Breaking the instrument seal, improper use or installation, accident, water damage, abuse, unauthorized repairs or alterations voids this warranty. AutoMeter Resellers please visit www.autometer.com/autometerlocator/index/unauthorized.

FOR SERVICE SEND TO: **AUTOMETER PRODUCTS, INC.** 413 West Elm Street, Sycamore, IL 60178 USA (866) 248-6357 Email us at service@autometer.com



