'EXPOSED RACKS' INSTALLATION GUIDE [8-00-9654-BK, 8-00-9754-BK, 8-00-9754-RD, 8-00-9656-BK, 8-00-9756-BK, 8-00-9756-RD] FOR 2018 – PRESENT JL (2 dr) & JLU (4dr) JEEP WRANGLER WITH SOFT TOP v.2019M04D15V2

PACKAGE	XBARS / BRACKET	PICTURE (of one)	HARDWARE	PICTURE (of one)
8-00-9654-BK, 8-00-9754-BK(RD), 8-00-9656-BK 8-00-9756-BK(RD)	8-00-9651, or 8-00-9751	51"	8-00-9605	83877
	8-00-9914 (JL 2dr & JLU 4dr)	The state of the s	^	9 C O F E
	8-00-9652 or 8-00-9752	48"	8-00-9605	11088
	8-00-9911 (JLU 4dr) or			
	8-00-9912 (JL 2dr)		(((CO))O	(((CO)))

TOOLS NEEDED:

PARTS ID:

- Adjustable


Wrench (not incl.),

- Allen Key (incl.)
- Jeep's TorxRatchet (incl. w/ Jeep)

BEFORE STARTING:

UNPACK

Fully Lower Soft
Top on Jeep. Open
& unpack all EXR
items



STEP 1 – FOR JL & JLU INSTALL FRONT BOLTS FIRST (8-00-9914)

Hardware:



For Bolt Positions 1 and 2,

1) Remove Jeep OE Bolts and washer (x4)



2) Replace with EXR Bolts (A) (x4) and Washer (C) (x4)



Use Allen Key (E) to hand tighten, snug. Do not overtighten.

- 3) Thread one Nut (B) on top of each EXR bolt and tighten down (x4). Do not overtighten.
- 4) Place one Washers (C) on top of each EXR Bolt & Nut (x4)
- 5) Place Front brackets (8-00-9914) in position on both sides (see picture for reference).




!!! WARNING !!! FRONT CROSSBAR MUST BE POSITIONED CLOSE TO FRONT WINDSHIELD. SERIOUS INJURY CAN OCCUR IF BAR IS WRONGLY PLACED OVER DRIVER / PASSENGER HEAD. CHECK BRACKETS ARE ON CORRECT SIDES.

- 6) Place Washers (C) on top of each bolt (x4)
- 7) Thread Lock Nuts (D) on top of each bolt (x4). Tighten, but do not overtighten.



SEE PICTURE
OF SAMPLE
FINISHED
BOLT /
BRACKET
ASSEMBLED




STEP 3a – INSTALL MID BRACKETS BOLTS FOR JLU (4DR) (8-00-9911) * FOR JL (2DR), SKIP TO STEP 3b

Hardware:



- 8) For Bolt Position 3, Follow steps 1-7 above
- 9) For Bolt Position 4, leave the JEEP OE bolt in place! → You will use the EXR Bolt in the larger hole directly behind the Jeep OE Bolt
 - *This is very similar to the other bolts, except you use a large flat washer (F) and rubber washer (G) included with the Mid Brackets Kit (8-00-9911)
 - a. Place (F) and (G) on Bolt (A), then slide bolt up through the ¾" hole such that the rubber washer sits against the painted Jeep frame.
 - b. On the top side, place (G) and (F) on top of the bolt such that the rubber washer sits against the painted Jeep frame
 - c. Loosely tighten down (B) nut on top of the bolt. Center bolt. Tighten further, but do not overtighten.
- 10) Follow Steps 4-7 (as above) to secure brackets. See below for Bolt / Bracket Positions





STEP 3b – INSTALL MID BRACKETS BOLTS FOR JL (2DR) (8-00-9912 hardware) * IF JLU (4 DR), SKIP TO STEP 4




For Bolt Positions 3 and 4 on the JL (2 door)

- 11) Remove the Jeep factory Bolt using Jeep's Torx driver.
- 12) Add 6 spacer washers (C) on top of plastic housing (x4).
- 13) Place Bracket on top of spacers, insert Jeep's bolt (x4), and tighten down. Make snug, but do not overtighten.




STEP 4 – INSTALL CROSSBARS (8-00-9905 hardware)

14) 3/8" Carriage Bolts slide though square bracket holes, through the crossbar (bar not present in picture to the right), then out the other side of the square bracket hole, followed by Flat washer, Locker Washer, then the 3/8" Nut. Tighten down fairly well ensuring the lock washer compresses and the bracket tab flexes and grips the crossbar. Crossbar should have no movement once tightened.



- 15) Install the 51" Crossbar (8-00-9651 or 8-00-9751) on the Front Brackets (8-00-9914)
- 16) Install the 48 "Crossbar (8-00-9652 or 8-00-9752) on the Mid Brackets (8-00-9911 or 8-00-9912)



The O'Land Crossbars come with a series of threaded holes on the bottom that allow for the weight distribution feet to be used on the hard top (not used on soft top configuration here). These same holes allow user to mount just about anything to the underside of the crossbar (e.g. light switch panel, CB Radio, etc.). Please see our website for updates and kits available.

IMPORTANT: IT IS THE RESPONSIBILITY OF THE INSTALLER/USER TO DECIDE WHERE AND HOW MUCH WEIGHT TO DISTRIBUTE IN ANY ONE LOCATION. IN THIS SETUP THE WEIGHT IS DISTRIBUTED DOWN THROUGH THE FRAME AND IS FANTASTICALLY STRONG. THAT BEING SAID, WEIGHT CAPACITY IS LIMITED TO JEEP'S MAXIMUM STATIC AND DYNAMIC WEIGHT LIMITS. WHEN PUTTING LOAD ON THE ROOF TOP, TAKE CAUTION TO ALWAYS DISTRIBUTE THE WEIGHT AS MUCH AS POSSIBLE. USE COMMON SENSE WHEN INSTALLING AND CARRYING LOADS. EXR CROSSBARS ARE THE

'EXPOSED RACKS' INSTALLATION GUIDE [8-00-9654-BK, 8-00-9754-BK, 8-00-9754-RD, 8-00-9656-BK, 8-00-9756-BK, 8-00-9756-RD] FOR 2018 – PRESENT JL (2 dr) & JLU (4dr) JEEP WRANGLER WITH SOFT TOP v.2019M04D15V2 STRONGEST ON THE MARKET, BUT INSTALLATION OF CROSSBARS DOES NOT MAKE YOUR VEHICLE INVINCIBLE, AND THEY DO NOT PROTECT YOU IN THE EVENT OF A VEHICLE ROLL OVER OR OTHER IMPACT. PLEASE USE COMMON SENSE IF YOUR LIFE EXPERIENCE HAS PROVEN TO YOU THAT OTHERS MAY HAVE MORE COMMON SENSE (SUCH AS A SPOUSE), PLEASE CONSULT THIS PERSON FOR JUST ABOUT EVERYTHING. :-)

BEFORE EACH USE (DRIVE), ALWAYS CHECK ALL BOLTS FOR TIGHTNESS AND CHECK THE POSITION AND STRAPS/BOLTS/PINS OF THE LOAD BEING CARRIED. WHENEVER LOADING SOMETHING ON TOP OF THE CROSSBARS FOR THE FIRST TIME YOU SHOULD STOP THE VEHCILE AFTER A FEW MINUTES OF DRIVING TO CHECK/TIGHTEN EVERYTHING (THIS IS FOR ALL ITEMS ON ALL ROOF RACKS, NOT JUST EXR).

Thank you for purchasing Exposed Racks crossbars. Please use these crossbars for awesome activities, take pictures, and share (#exposedracks, @smsautopartsco). Your crossbars were MADE IN AMERICA, and MADE IN PENNSYLVANNIA (not just designed, or assembled... but actually completely made here, by SMS Auto Parts, Co. – from raw steel all the way through to final packaging). You personally supported our dedicated employees as well as Breast Cancer Awareness with your purchase. Our business model is to reinvest into and grow our business and we look forward to having you as a lifetime customer. Sincerely, the 'EXR' Team

LIMITED WARRANTY

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS AND YOU MAY ALSO HAVE OTHER RIGHTS, WHICH VARY FROM STATE TO STATE. THIS LIMITED WARRANTY CAN ALSO BE FOUND AT WWW.SMSPARTS.COM/WARRANTY AND IN THE DOCUMENTATION WE PROVIDE WITH THE PRODUCTS. WE WARRANT THAT DURING THE WARRANTY PERIOD, THE PRODUCTS PURCHASED FROM THE SITE WILL BE FREE FROM DEFECTS IN MATERIALS AND WORKMANSHIP. WE LIMIT THE DURATION AND REMEDIES OF ALL IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, TO THE DURATION OF THIS LIMITED WARRANTY. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU. OUR RESPONSIBILITY FOR DEFECTIVE PRODUCTS IS LIMITED TO REPAIR, REPLACEMENT OR REFUND AS SET FORTH IN THIS WARRANTY STATEMENT. NEITHER ANY PERFORMANCE OR OTHER CONDUCT, NOR ANY ORAL OR WRITTEN INFORMATION, STATEMENT OR ADVICE PROVIDED BY US OR ANY OF OUR SUPPLIERS, AGENTS OR EMPLOYEES WILL CREATE A WARRANTY, OR IN ANY WAY INCREASE THE SCOPE OR DURATION OF THIS LIMITED WARRANTY.

Who May Use This Warranty?

This limited warranty extends only to the original purchaser of products and services from the Site. It does not extend to any subsequent or other owner or transferee of the product or any transferee or other beneficiary of the service.

What Does This Warranty Cover?

This limited warranty covers during the Warranty Period (as defined below) defects in materials and workmanship in products and services purchased from the Site.

What Does This Warranty Not Cover?

This limited warranty does not cover any damages due to: transportation; storage; improper use; failure to follow the product instructions, guidelines or to perform any preventive maintenance; modifications of or any types of repairs to the product and/or a load system carrier other than those authorized by SMS; combination or use with any products, materials, processes, systems or other matter not provided or authorized in writing by SMS Auto Parts, Co.; unauthorized repair; normal wear and tear; cosmetic rust, and scratches; external causes such as accidents, abuse, intentional or unintentional deformation of parts, unlawful vehicle operation, or other actions or events beyond our reasonable control.

What is the Period of Coverage?

This limited warranty starts on the date of your purchase and lasts for a THREE YEAR TIME PERIOD the "Warranty Period". The Warranty Period is not extended if we repair or replace a warranted product or re-perform a warranted service. We may change the availability of this limited warranty at our discretion, but any changes will not be retroactive.

What Are Your Remedies Under This Warranty?

With respect to any defective products during the Warranty Period, we will, in our sole discretion, either: (i) repair or replace such products (or the defective part) free of charge or (ii) refund the purchase price of such products.

How Do You Obtain Warranty Service?

To obtain warranty service, you must call 215-310-1917 or email our Customer Service Department at support@smsparts.com during the Warranty Period to obtain an RMA number. No warranty service will be provided without an RMA number. Any refunds will go through the authorized distributor, vendor, seller, retailer, re-seller, or website from where the original parts were purchased. Parts must be purchased from an authorized retailer to qualify for a warranty claim.

Limitation of Liability

THE REMEDIES DESCRIBED ABOVE ARE YOUR SOLE AND EXCLUSIVE REMEDIES AND OUR ENTIRE OBLIGATION AND LIABILITY FOR ANY BREACH OF THIS LIMITED WARRANTY. OUR LIABILITY WILL UNDER NO CIRCUMSTANCES EXCEED THE ACTUAL AMOUNT PAID BY YOU FOR THE DEFECTIVE PRODUCT OR SERVICE THAT YOU HAVE PURCHASED THROUGH THE SITE, NOR WILL WE UNDER ANY CIRCUMSTANCES BE LIABLE FOR ANY LOSS OF PRODUCTION, WORK, DATA, USE, BUSINESS, GOODWILL, REPUTATION, REVENUE OR PROFIT, ANY DIMINUTION IN VALUE, COSTS OF REPLACEMENT GOODS OR SERVICES, OR ANY CONSEQUENTIAL, INCIDENTAL, SPECIAL OR PUNITIVE DAMAGES OR LOSSES, WHETHER DIRECT OR INDIRECT.

THIS WARRANTY IS IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.

SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.