



# Quadratec® Bracket Kit for Roof Rack

Installation Manual: for '18 - Current Wrangler JL, JLU & Gladiator JT #92034.1092



## PARTS LIST:

Gutter Mount Bracket	QTY 4
Gutter Mount Bracket Clamp	QTY 4
88mm x 35mm x 5.5mm Foam Pads	QTY 4
88mm x 12mm x 3.2mm Foam Pads	QTY 4
88mm x 25mm x 3.2mm Foam Pads	QTY 4
M8 x 1.25 x 25 Captured Washer Bolt Combo	QTY 8
M8 x 1.25 x 25 Hex Head Bolt	QTY 8
M8 x 24mm OD Flat Washer	QTY 20
M8 x 16mm OD Flat Washer	QTY 6
M8 Nylon Lock Nut	QTY 12

## REQUIRED TOOLS:

Safety Glasses  
Ratchet Handle Wrench  
13mm Shallow and Deep Sockets  
13mm Box end or Ratcheting Wrench



**READ ALL SAFETY MESSAGES AND UNDERSTAND ALL INSTRUCTIONS BEFORE ATTEMPTING TO INSTALL THIS PRODUCT. ALWAYS WEAR SAFETY GLASSES DURING INSTALL.**

**Quadratec®**  
The Jeep® Experts

**A Few Words About Product Safety:**  
Your Quadratec® Roof Rack Bracket Kit is intended to enhance the utility of your off road capable vehicle. Before installation, please review the following safety information and installation recommendations.

Throughout these instructions important safety information is generally preceded by one of three signal words indicating the relative risk of injury, property damage or adverse consequence. The signal words mean:

**⚠ WARNING ⚠**

A HAZARDOUS SITUATION WHICH, IF NOT AVOIDED, COULD RESULT IN DEATH OR SERIOUS INJURY. YOU CAN BE KILLED OR SERIOUSLY HURT IF YOU DON'T FOLLOW INSTRUCTIONS.

**⚠ CAUTION ⚠**

A HAZARDOUS SITUATION WHICH, IF NOT AVOIDED, COULD RESULT IN MINOR OR MODERATE INJURY. YOU CAN BE MODERATELY HURT AND ALSO MAY SUFFER PROPERTY DAMAGE IF YOU DON'T FOLLOW INSTRUCTIONS.

**NOTICE**

CAREFUL ATTENTION IS REQUIRED TO THIS INSTRUCTION OR OPERATION BUT DOES GENERALLY NOT RELATE TO PERSONAL INJURY. DAMAGE TO YOUR PRODUCT OR OTHER PROPERTY MAY RESULT IF YOU DON'T FOLLOW INSTRUCTIONS.

**Before You Begin Installation:**  
Congratulations on your purchase of Quadratec® Roof Rack Bracket Kit for your Jeep® Wrangler Vehicle. These products have been designed for long life and a great performance under the toughest conditions.

When unpacking, check to make sure all parts are included and not damaged due to shipping. If any part is missing or broken, please call Customer Service at 800-745-6037 as soon as possible.

Thank you again for your purchase and let's start the installation process.

**⚠ CAUTION ⚠**

READ ALL SAFETY MESSAGES AND ALWAYS WEAR SAFETY GLASSES WHEN WORKING WITH TOOLS.

**⚠ WARNING ⚠**

DO NOT EXCEED 150 POUNDS OF EVENLY DISTRIBUTED CARGO LOAD. FOLLOW FACTORY OWNERS MANUAL RECOMMENDATIONS FOR ROOF LOAD CAPACITY AT ALL TIMES.

**⚠ WARNING ⚠**

AFTER INSTALLATION, CHECK AND RE-TORQUE ALL FASTENERS ON THE MOUNTING BRACKETS AND RACK ASSEMBLY.

**⚠ WARNING ⚠**

ALL MOUNTING BRACKETS AND CLAMPS MUST BE PLACED AS SHOWN IN THESE INSTRUCTIONS TO ACHIEVE THE STATED LOAD CAPACITY. PLEASE VIEW ALL IMAGES IN THIS BOOKLET BEFORE YOU BEGIN INSTALLATION.

**NOTICE**

YOU WILL ASSEMBLE YOUR ROOF RACK WITH THE INSTRUCTIONS SUPPLIED WITH THAT PRODUCT.

**Quadratec®**  
The Jeep® Experts

**Installation Instructions:**



*Put on safety glasses. Start by applying foam pads to the required areas. The 88mm long and narrow pads will be applied to the Bracket clamps as shown. (FIG 1)*



*The 70mm short pads will be applied to the main brackets foot as shown. (FIG 2) The pad needs to wrap around the foot evenly to protect your hard tops finish.*



*The 88mm long thicker pads will be applied to the main brackets base as shown to protect your hard tops finish. (FIG 3)*



*Start by laying the main bracket in the drip rail channel on your hard top. (FIG4) Both pads should contact the top as shown.*



*Loosely install the brackets clamp to the main bracket as shown with an M8 washer and locking nut using a 13mm deep socket. (FIG 5)*




*Loosely install 2 of the supplied M8 captured washer bolts through the slots and into the main bracket as shown using a 13mm socket. (FIG 6) Repeat steps 1-6 for all remaining brackets*

**Installation Instructions:**



Once rack is assembled per its directions, with help from an assistant lift it up onto the brackets carefully aligning all the mounting slots. (FIG 7)



Loosely attach rack to brackets with the supplied M8 hex head bolts, washers and lock nuts. Each bolt will get two washers, one top and one bottom. (FIG 8)



Once you have the rack in its desired location start by snugging the main brackets to the hard top. Bring the brackets clamp side mounting hardware just tight enough so it can still slide in the slots. (FIG 9)



Now snug the top mounting stud using a 13mm deep socket. (FIG 10) Lastly tighten the side mounting bolts using a 13mm socket.

**Installation Instructions:**

**RESULTS for GLADIATOR JT**



**RESULTS for WRANGLER JL**



*Check to make sure your rack is centered to your liking and now you may tighten all M8 hex head hardware*

*through the rack and brackets using a 13mm socket and box end wrench. Installation is now complete.*

***Quadratec***  
The Jeep Experts

# Quadratec® Exclusive Three Year Limited Warranty

Your Quadratec® branded accessories are covered by the following **Limited Warranty** provided exclusively by Quadratec, Inc., 1028 Saunders Lane, West Chester PA 19380.

This Limited Warranty is the only warranty made in connection with your purchase. Quadratec neither assumes nor authorizes any vendor, retailer or other person or entity to assume for it any other obligation or liability in connection with this product or Limited Warranty. This Limited Warranty does not apply and is not cumulative to any accessory or part distributed by Quadratec for which the Manufacturer provides a separate written warranty.

**What is Covered:** Subject to the terms, exclusions and limitations herein and with respect only to Quadratec branded accessories first sold in the United States, Quadratec warrants to the initial retail purchaser only that your Quadratec accessory shall be free of defects in material and workmanship: **for a period of three (3) years from date of retail purchase.**

This **Limited Warranty** is not assignable and shall terminate upon sale of the vehicle upon which the Quadratec accessory is installed or other transfer third persons.

All other warranties are hereby disclaimed, except to the extent prohibited by applicable law in which case any implied warranty of merchantability or fitness for a particular purpose on this product is limited to 3 year from date of initial retail sale. Quadratec reserves the rights to: (a.) require invoice or other proof your accessory is within the terms of this **Limited Warranty** as a condition of warranty service and, (b.) make future revisions to this product and **Limited Warranty** without prior notice or obligation to upgrade your product.

**What is Not Covered:**

Your Quadratec **Limited Warranty** does not cover products or parts Quadratec determines to have been damaged by or subjected to:

(a.) installation damage, alteration, modification, combination with other parts, failure to maintain or improper repair or service, (b.) normal wear & tear, cosmetic damage or damage from moisture or water immersion, (c.) Acts of God, accidents, misuse, negligence, inadequate mounting or impact with vehicle(s), obstacles or other aspects of the environment, (d.) theft, vandalism or other intentional damage.

**Remedy Limited to Repair/Replacement:** **The exclusive remedy provided hereunder shall, upon Quadratec inspection and at Quadratec's option, be either repair or replacement of product or parts (new or refurbished) covered under this Limited Warranty.** Customers requesting warranty consideration should first contact Quadratec to obtain a RGA number (610-701-3336). All labor, removal, shipping and installation costs are customer's responsibility.

**Other Limitations - Exclusion of Damages - Your Rights Under State Law:**

In consideration of the purchase price paid, neither Quadratec nor any independent Quadratec distributor/licensee are responsible for any time loss, rental costs, or for any incidental, consequential, punitive or other damages you may have or incur in connection with any part or product purchased. Your exclusive remedy hereunder for covered parts is repair/replacement as described above.

This **Limited Warranty** gives you specific rights. You may also have other rights that vary from state to state. For example, some states do not allow limitations of how long an implied warranty lasts and /or do not allow the exclusion or limitation of incidental or consequential damages, so the limitations and exclusions herein may not apply to you.

©Quadratec, Inc. 2020. All Rights Reserved.  
8.31.20 A4 Version

Part #12999.3176

