





# **INSTALL INSTRUCTIONS**

**Application: 2018+ Jeep Wrangler JL** 

2020+ Jeep Gladiator JT

## JL / JT LIGHT PILLAR MOUNT:

518LMP0B, 518LMP1B,

(RIGID ADDAPT 50" SKU: 250413 ONLY)

518ALMP0B (RIGID ADDAPT) & 518ALMP1B (RIGID ADDAPT)



#### **WARNING**

Read the instructions completely before beginning installation. Before tightening bolts, drilling or cutting where required, check to make sure there are no obstructions such as brake, fuel or electrical lines which may be damaged. Also keep in mind this is an aftermarket product and MAY require minor shimming and/or trimming, reaming, etc. for proper fit. Road Armor is not responsible for any damages to vehicle.

#### **(1) IMPORTANT NOTICE**

- Be sure to inspect and test fit your product to ensure proper fitment before having it coated, painted, bed lined, etc.
- Road Armor will not be responsible for the cost of coating your unit if any problems with fit or finish are not noted and addressed beforehand.

#### **SAFETY FIRST!**

- FOLLOW ALL INSTRUCTIONS, YOUR SAFETY AND THE SAFETY OF OTHERS IS MOST IMPORTANT.
- WEAR APPROPRIATE EYE PROTECTION AND EXERCISE CAUTION WHEN DRILLING / CUTTING

# **REQUIRED TOOLS**

Metric and SAE Socket Sets and Wrenches Drill & Unibit

## **Available Accessories**

518APLAB: 50-Inch Light Arch Bracket (used with kit 518LMP#B ONLY)

Light Arch Bracket REQUIRED to mount multiple configurations of single "surface mount" lights.

### INCLUDED HARDWARE

- (12) 5/16"x 3/4" Bolts
- (12) 5/16" Flange Nuts
- (16) 5/16" Washers
- (1) PSG COWL
- (1) DVR COWL
- (1) PSG LIGHT MOUNT
- (1) DVR LIGHT MOUNT



Remove 4 - 8mm bolts securing each OEM cowl.

After cowl is removed; tape 2 - 5/16" washers over back lower holes as shown below

Loosely assemble cowl and light mount with 6 - 5/16" bolt and flange nuts.

Install light mount assembly onto cowl using 8mm OEM bolts.

Install light running wiring inside the upright

Tighten all hardware at this time. (\*Be sure pillar brackets are not rubbing on windshield\*)

