



Warrior, Inc.
11100 SW Industrial Way
Tualatin, OR 97062
Phone: (888) 220-6861
Fax: (503) 692-0364

customerservice@warriorproducts.com
www.warriorproducts.com

JEEP WRANGLER SAFARI FRONT LIGHT BAR

INSTALLATION INSTRUCTIONS

P/N: 844 / 869 / 872

Due to welding, handling, shipping, etc., the legs may need to be “adjusted” slightly (bent in or out) to fit correctly. A small amount of twisting will not hurt the bar. Be careful not to scratch the paint as you install the legs.

NOTE: The nut plates on some Jeep windshields may come loose when both bolts are removed at the same time. Loosen both bolts, remove one, install bracket with one bolt, spin out of the way and remove other bolt. Try to keep one bolt engaged through the windshield at all times.

1. Remove the 2 screws on the upper outboard side of the driver’s side windshield hinge. Repeat for the passenger side hinge as well. New screws are provided.
2. Assemble the Light Bar by inserting windshield mounting brackets onto the short light bar hoop and inserting snapper pins to hold in place. For a more permanent install we recommend the use of the included $\frac{1}{4}$ ” x $1\frac{1}{4}$ ” bolts, washers, and Nyloc nuts. The light tabs should be facing forward and the windshield mounting brackets towards the rear of the vehicle.
3. Place the front Light Bar assembly onto the windshield. Install screws through the Light Bar mounting brackets.
4. Lights should be installed per the manufacturer’s instructions.

If you need further assistance installing your product, please contact us by email at customerservice@warriorproducts.com or call us at (888) 220-6861.

THANK YOU FOR PURCHASING WARRIOR PRODUCTS



WARRIORPRODUCTS.COM

